





NOTE:  
1. ALL SIGNAL GROUNDS ARE BUSSED IN PCB.

IPASS™ IS A TRADEMARK OF MOLEX.

ITEM	DESCRIPTION	L (mm)	QTY.
K	Braid sleeving	280REF	1
J	2x28AWG-S:SHLD:PVC:RD:-40C~85C:S-ATA	3220REF	
I	BLACK PVC	A/R	
H	BLCK TAPE	A/R	2
G	LABEL		4
F	HST F 12MM 125C (UL) BLK	A/R	2
E	SINGLE ATA CONN.		4
D	36CKT PCB		1
C	PE MATERIAL	A/R	
B	PBT	A/R	
A	LATCH		1

<b>ENTER DESCRIPTION</b> EC NO: USY2011-0509 DRWN: ZYYU 2011/01/14 CHKD: ARES FENG 2011/01/14 APPR: CLAN01 2011/01/14 B	<b>QUALITY SYMBOLS</b> ▽=0 ▽=0	<b>GENERAL TOLERANCES (UNLESS SPECIFIED)</b>		<b>DIMENSION STYLE</b> MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		4 PLACES	± ---	± ---	DRAWN BY	DATE	TITLE 36CKT IPASS STR -(4)SATA, SAS 2.0			
		3 PLACES	± ---	± ---	ZYYU	2010/12/13				
		2 PLACES	± 0.13	± ---	CHECKED BY	DATE	MOLEX INCORPORATED			
1 PLACE	± 0.25	± ---	ARES FENG	2010/12/13						
ANGULAR ±1/2°		APPROVED BY		DATE	MATERIAL NO. 1110961052		DOCUMENT NO. SD-111096-009		SHEET NO. 2 OF 2	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				