


注記 NOTES

- 1 嵌合相手: 51004-\*\*\*00  
MATES WITH : 51004-\*\*\*00
  - 2 6極以上にのみ適用する。  
DOTTED LINE TYPICAL 6 THRU  
12 CIRCUIT WAFER ONLY.
  - 3 3極このみ適用する。  
3 CIRCUIT WAFER ONLY.
  - 4 ロック窓は、2及び3極に1個  
4極以上は、2個とする。  
ONE LOOKING WINDOW, FOR 2&3CKT.  
TWO LOOKING WINDOW, FOR 4CKT. &  
MORE THAN 4CKT.
  - 5 成形成材料 RESIN MATERIAL  
ASAHI CHEMICAL INDUSTRY CO.,LTD  
66NYLON FG101 UL94V-0  
UL FILE NO.E48285
- △ キングはトレードマーク側から見て奇数極につける事  
KINK TO BE ADDED ON THE ODD NUMBER  
SOLDER TAILS. (FROM THE TRADE MARK  
SIDE)



25.5	22	26	25	22	53025-1210	12
23.5	20	24	23	20	-1110	11
21.5	18	22	21	18	-1010	10
19.5	16	20	19	16	-0910	9
17.5	14	18	17	14	-0810	8
15.5	12	16	15	12	-0710	7
13.5	10	14	13	10	-0610	6
11.5	8	12	11	8	-0510	5
9.5	6	10	9	6	-0410	4
7.5	4	8	7	4	-0310	3
5.5	2	6	5	2	53025-0210	2
E	D	C	B	A	ENG. NO.	CKT.

REVISED EC NO: JTR2011-0119 DRWN:SHIBATA 2011/08/18 CHKD:HKOMATSU 2011/08/18 APPR: MAYAMOTO 2011/08/31	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
	10 UNDER ±0.20	10 OVER 30 UNDER ±0.25	30 OVER ±0.30	DRAWN BY M. NAKAMURA	DATE 1994/08/19	TITLE 2.0 LOW PROFILE CONN WAFER ASSY (B/E TYPE)		
	ANGULAR ±3 °			CHECKED BY H. HIRAMOTO	DATE 1994/08/20	MOLEX INCORPORATED		
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			APPROVED BY M. FUKUSHIMA	DATE 1994/08/20	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-53025-**-10	SHEET NO. 1 OF 1