

# Material Declaration for M402VF-3-032-05NR

Product Information	
Part Number:	M402VF-3-032-05NR
Part Description:	0.5mm Pitch female conn.
Part Weight (g):	0.285

Process Data	
Peak Reflow (Deg. C)	260°C for 10 seconds
Termination Finish	100% Tin over Nickel
RoHS Compliant? (Y/N)	Yes

Note: Tin plating is subject to 1,000ppm max Lead impurity.

Homogeneous Material Location	Weight (g)	Tolerance	Substance Name	CAS #
Contacts - Phosphor Bronze	0.0707	5%	Copper	7440-50-8
	0.00371	1%	Tin	7440-31-5
	0.00016	0.5%	Phosphorus	7723-14-0
	0	0.00016g max	Nickel (impurity only)	7440-02-0
	0	0.00016g max	Zinc (impurity only)	7440-66-6
	0	0.000064g max	Iron (impurity only)	7439-89-6
	0	0.000016g max	Lead (impurity only)	7439-92-1
Contacts - Plating	0	0.000384g max	Other Impurities	
	0.00237	10%	Nickel	7440-02-0
Retainers - Brass	0.0024	20%	Tin	7440-31-5
	0.00683	3%	Copper	7440-50-8
	0.00401	2%	Zinc	7440-66-6
	0	0.00001g max	Lead (impurity only)	7439-92-1
	0	0.00001g max	Iron (impurity only)	7439-89-6
	0	0.00001g max	Tin (impurity only)	7440-31-5
	0	0.000032g max	Nickel (impurity only)	7440-02-0
	0	0.000006g max	Aluminium (impurity only)	7429-90-5
	0	0.00001g max	Other Impurities	
	0.000274	10%	Nickel	7440-02-0
Retainers - Plating	0.00028	10%	Tin	7440-31-5
Moulding (total weight)	0.194	6%	33% GF LCP	
Containing:	0.13	6%	Liquid Crystal Polymer	
	0.064	6%	Glass Fibre	65997-17-3
Does not contain:			Other Brominated Flame Retardants	
			Antimony	

Prepared by: *M. J. Perry*

Martin J Perry, BSc(Eng) MSc CEng MIET  
Compliance Specialist  
ComplianceTeam@harwin.co.uk

On behalf of: **HARWIN**