

6

5

4

3

2

1

F3 MAX-LOC NUT

STAINLESS STEEL SCREWS W/LOCK WASHER (4) REQ'D

STAINLESS STEEL SCREWS W/FLAT WASHER 1ST AND O'RING

STAINLESS STEEL SUPPORT RINGS (2) REQ'D

7.41"

MOMENTARY ON/OFF 1NO/1NC (505SW-M) NOT INTERLOCKED

1.18" BETWEEN CENTERS

1.76"

3.52"

2.31"

NOTES:

1. INSTALLATION INSTRUCTIONS, BUTTON ID. LABELS. ARE PACK WITH THE PART.
2. ALL BUTTONS ARE HIGH AMBIENT, CHEMICALLY RESISTANT MATERIAL - COLOR BLACK

| | | | | | | | | | |
|--|-----------------|--|-------------------------|------------------------|---|--------------------------------------|-------------------|------------------------|--|
| RELEASE DRAWING EC NO: WNA2009-0485 DRWN: TVICKERS 2/2/09 CHKD: --- APPR: DTTIUS 2009/02/06 DESCRIPTION | QUALITY SYMBOLS | GENERAL TOLERANCES (UNLESS SPECIFIED) | | DIMENSION STYLE INCHES | | SCALE NTS | DESIGN UNITS INCH | THIRD ANGLE PROJECTION | |
| | ▽=0 | mm | INCH | DRAWN BY TV | DATE 2009/02/02 | TITLE | | | |
| | ∇=0 | 4 PLACES ±---- | ±---- | CHECKED BY HK | DATE 2009/02/02 | 2 POS PENDANT 5052 W/(505SW-M) | | | |
| | | 3 PLACES ±---- | ±.005 | APPROVED BY DT | DATE 2009/02/02 | | | | |
| | 2 PLACES ±---- | ±.010 | MATERIAL NO. 1301260306 | | MOLEX INCORPORATED | | SHEET NO. 1 OF 1 | | |
| | 1 PLACE ±---- | ±.020 | ANGULAR ±.5° | | DOCUMENT NO. SD-130126-023 | | | | |
| | | DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS | | SIZE A | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | |

6

5

4

3

2

1