


**PLUG MML H2.5-JACK SMA BULKHEAD**


**R302.255.000 XXX**

**CABLE 1.33/50S-BR,LENGTH=XXX MM**

Series : MML




Length=XXX	Step	Tolerance
30 to 100	10	±2
110 to 200		±3
225 to 300	25	±5
325 to 400		±10



E.g. XXX=070 means length is 70±2, the part number is R302.255.000 070

All dimensions are in mm.



- \* 1 \* Connector A : **MML H2.5 PLUG (gold plated)**
- \* 2 \* Connector B : **SMA JACK BULKHEAD(gold plated)**
- \* 3 \* Cable : **1.33/50S BLACK**


**ELECTRICAL CHARACTERISTICS**

Impedance	<b>50 Ω</b>
Frequency	<b>0-6 GHz</b>
Operating temperature	<b>-40/+90 ° C</b>
VSWR	<b>1.3 ** + 0.00 x F(GHz) Maxi</b>
Insertion loss	<b>0.73* √F(GHz) dB Maxi</b>
Voltage rating	<b>250 Veff Maxi</b>
Dielectric withstanding voltage	<b>300 Veff mini</b>
Insulation resistance	<b>500 MΩ mini</b>

**SPECIFICATION**

Weight	<b>3* g</b>
Cable retention	<b>4 N mini</b>
Mating life	<b>30 cycles</b>
Others : **VSWR up to 3GHz	<b>1.3 max</b>
up to 6GHz	<b>1.5 max</b>

**Mating status**



Mated with MML receptacle  
R302.302.000

Length	*Insertion loss(Maxi)	*Weight(Maxi)
30 to 90	0.73 dB	3.00 g
100 to 200	1.16 dB	3.50 g
225 to 400	2.02 dB	4.00 g

**Edition : 1337 A**

Design changes may be in order to improve the product.

*This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from RADIALL*

