




| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 30.8              |
| B1  | 14.3              |
| B2  | -                 |
| C   | 23.05             |
| D   | 4                 |
| E   | 72                |
| F   | 34.8              |
| G   | 31.7              |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICKTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |
| 12  | ENDGEHÄUSE / ENDBELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

| Material Specification:                        |
|--|
| Shell Material: Aluminium alloy                |
| Shell Plating: Zinc cobalt, black (conductive) |
| Insulator Material: CR-Elastomere              |
| Contact Material: Copper alloy                 |
| Contact Plating: Hard silver                   |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
 CUSTOMER



description CA3101E18-4P-B-F80-A232  
 Cable connecting plug  
 Endbell with clamp and bushing  
 AWG Crimp / Pin / Layout: 18-4

© All rights reserved. Reproduction or issue to third in any form  
 whatever is only permitted with written authorization of ITT Cannon

page 1/1  
 revision 1730 14. May 19