

826

STATIC OFF™ ANTISTATIC FOAMING SPRAY

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Identifier:** 826**Other Means of Identification:** Static Off™ Antistatic Foaming Spray**Related Part #** 826-450G

### Recommended Use and Restriction on Use

**Use:** Antistatic spray**Uses Advised Against:** Not available

### Details of Manufacturer or Importer

**Manufacturer**

MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADA

MG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA

**☎** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** [support@mgchemicals.com](mailto:support@mgchemicals.com)**WEB** [www.mgchemicals.com](http://www.mgchemicals.com)**☎** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** [info@mgchemicals.com](mailto:info@mgchemicals.com)**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents)  
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**  
(Service access code: 335388)


**For emergencies involving the transport of dangerous goods;** 24/7 service  
CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones

**826**
**STATIC OFF™ ANTISTATIC FOAMING SPRAY**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Gas Under Pressure	Liquefied gas	Warning	Gas cylinder

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H280: Contains gas under pressure; may explode if heated
<b>Prevention</b>	<b>Precautionary Statements</b>
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, flames, and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
<b>Storage</b>	<b>Precautionary Statements</b>
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of container in accordance to local, regional, national, and international regulations.

*Note:* Contains 10% flammable ingredients mixed with water.

*Section continued on the next page*

**826**
**STATIC OFF™ ANTISTATIC FOAMING SPRAY**
**Hazards Not Otherwise Classified**

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.	Warning	None

**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
7732-18-5	water	90%
75-28-5	isobutane	4%
67-63-0	propan-2-ol	3%
111-76-2	2-butoxyethanol	2%
74-98-6	propane	1%

**Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code/Symptoms/Precautionary Statements</i>
<b>IF IN EYES</b>	P305 + P351 + P338
<b>Immediate Symptoms</b>	<i>low toxicity</i>
<b>Response</b>	Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>IF INHALED</b>	P304 + P340
<b>Immediate Symptoms</b>	<i>low toxicity</i>
<b>Response</b>	Remove person to fresh air and keep comfortable for breathing.
<b>IF ON SKIN</b>	P302 + P352
<b>Immediate Symptoms</b>	<i>low toxicity</i>
<b>Response</b>	Wash with plenty of water.
<b>IF SWALLOWED</b>	P301 + P330, P331, P312
<b>Immediate Symptoms</b>	<i>low toxicity</i>
<b>Response</b>	Rinse mouth. Do NOT induce vomiting. If you feel unwell: Call a POISON CENTER or doctor.

826

**STATIC OFF™ ANTISTATIC FOAMING SPRAY****Section 5: Fire-Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use extinguishing media suitable for surrounding materials.  Use water spray to cool containers.
<b>Specific Hazards</b>	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection recommendations in Section 8.
<b>Precautions for Response</b>	Remove or keep away all sources of extreme heat or open flames.
<b>Environmental Precautions</b>	Not applicable
<b>Containment Methods</b>	Not applicable
<b>Cleaning Methods</b>	If necessary, wash spill area with water.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**Section 7: Handling and Storage**

<b>Prevention</b>	Keep out of reach of children.  Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  Do not pierce or burn, even after use.
<b>Handling</b>	Do not spray on an open flame or other ignition source.  Wash hands thoroughly after handling.
<b>Storage</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].

**826**
**STATIC OFF™ ANTISTATIC FOAMING SPRAY**
**Section 8: Exposure Controls/Personal Protection**
**Substances with Occupational Exposure Limit Values**

<b>Chemical Name</b>	<b>Country/ Provinces</b>	<b>Long Term Exposure Limits (PEL)</b>	<b>Short Term Exposure Limits (STEL)</b>
isobutane <i>alkane (C2-C4)</i> <i>aliphatic hydrocarbon gas</i>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	See footnote <sup>a)</sup> Not established 1 000 ppm 1 000 ppm 800 ppm Not established	Not established Not established Not established Not established Not established Not established
propan-2-ol	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	200 ppm (TWA) 400 ppm 200 ppm 200 ppm 200 ppm 400 ppm	400 ppm Not established 400 ppm 400 ppm 400 ppm 500 ppm
2-butoxyethanol	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	20 ppm 50 ppm 20 ppm 20 ppm 20 ppm 25 ppm	Not established Not established Not established Not established Not established Not established
propane	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	See footnote <sup>a)</sup> 1 000 ppm 1 000 ppm 1 000 ppm 1 000 ppm 1 000 ppm	Not established Not established Not established Not established Not established Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS database<sup>2</sup> and from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Refer to the ACGIH Appendix F: Minimum Oxygen Content for Asphyxia TLV Basis

**Engineering Controls**
**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

*Section continued on the next page*

826

**STATIC OFF™ ANTISTATIC FOAMING SPRAY****Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**RECOMMENDATION:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

Use of protective gloves chemically resistant gloves if skin contact is likely.

Do NOT use latex rubber, polyvinyl alcohol (PVA) or PVC gloves.

**Respiratory Protection**

For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**826**
**STATIC OFF™ ANTISTATIC FOAMING SPRAY**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Liquid in aerosol format	<b>Lower Flammability Limit</b> <sup>a)</sup>	Not available
<b>Appearance</b>	Clear	<b>Upper Flammability Limit</b> <sup>a)</sup>	Not available
<b>Odor</b>	Alcohol-like	<b>Vapor Pressure @21 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	>1 (Air =1)
<b>pH</b>	Not available	<b>Relative Density @25 °C</b>	1
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Completely miscible
<b>Initial Boiling Point</b> <sup>a)</sup>	≥93 °C [199 °F]	<b>Partition Coefficient n-octanol/water</b>	Not available
<b>Flash Point</b> <sup>a)</sup>	≥50 °C [≥123 °F]	<b>Auto-ignition Temperature</b> <sup>b)</sup>	≥245 °C [≥473 °F]
<b>Evaporation Rate</b>	<1 (ButAc =1)	<b>Decomposition Temperature</b>	Not available
<b>Flammability</b>	Non Flammable	<b>Viscosity @40 °C</b>	<20.5 mm <sup>2</sup> /s

a) Lowest component literature value, which corresponds to 5% propan-2-ol

b) Lowest component auto-ignition literature value

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	Not available
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Open flames, temperatures above 50 °C [122 °F], and incompatible substances
<b>Incompatibilities</b>	Oxidizing agents, strong acids, strong bases
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**826**
**STATIC OFF™ ANTISTATIC FOAMING SPRAY**
**Section 11: Toxicological Information**
**Summary of Effects and Symptoms by Routes of Exposure**

<b>Eyes</b>	Low toxicity
<b>Skin</b>	May causes mild skin irritation.
<b>Inhalation</b>	Low toxicity
<b>Ingestion</b>	Low toxicity
<b>Chronic</b>	Not available

**Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	<b>LD50 oral</b>	<b>LD50 dermal</b>	<b>LC50 inhalation</b>
isobutane	Not applicable	Not applicable	>570 000 ppm 4 h Rat
propan-2-ol	3 600 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat
2-butoxyethanol	1 300 mg/kg Rat	>2 000 mg/kg Rat	>4.9 mg/L 3 h (vapor) Rat
propane	Not applicable	Not applicable	>800 000 ppm 4 h Rat

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA databases were consulted. The data from supplier SDS were also consulted.

*Section continued on the next page*



**826****STATIC OFF™ ANTISTATIC FOAMING SPRAY****Other Toxicological Effects****Skin corrosion/irritation**

The 2-butoxyethanol component is classified as a skin irritant, but it is not present in sufficient concentration to trigger classification.

**Serious eye damage/irritation**

Propan-2-ol and 2-butoxyethanol are severe eye irritants, but aren't present in sufficient concentration to trigger classification.

**Sensitization**  
(allergic reactions)

Based on available data, the classification criteria are not met.

**Carcinogenicity**  
(risk of cancer)

None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.

**Mutagenicity**  
(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

**Reproductive Toxicity**  
(risk to sex functions)

Based on available data, the classification criteria are not met.

**Teratogenicity**  
(risk of fetus malformation)

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Propan-2-ol is known to have narcotic effects, however, its concentration in the mixture is too low to trigger classification under GHS criteria.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Not an aspiration hazard under GHS. Does not contain any components classified as Cat 1 aspiration hazard.

**826****STATIC OFF™ ANTISTATIC FOAMING SPRAY****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Based on available data, propan-2-ol does not meet the environmental toxicant classification with LC50 and EC50 >100 mg/L.

- Propan-2-ol has a minimal LC50 96 h of 9 640 mg/L for Pimephales promelas (fathead minnow); an EC50 24 h of 5 102 mg/L Daphnia magna (water flea); and an EC50 72 h of 2 000 mg/L Desmodesmus subspicatus (green algae).
- The 2-butoxyethanol ingredient has a minimal LC50 96 h of 220 mg/L for Oncorhynchus mykiss (rainbow trout); and an EC50 72 h of 1 815 mg/L Desmodesmus subspicatus (green algae).

**Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds

**Chronic Ecotoxicity**

Available toxicity data does not meet classification thresholds

**Biodegradability**

Not available

**Other Effects**

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 8% [82 g/L]

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

826

STATIC OFF™ ANTISTATIC FOAMING SPRAY

**Section 14: Transport Information**

**Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);  
**USA CFR 49 Regulations** (Parts 100 to 185).

Sizes 1 L and under  
**Limited Quantity**



**Air**

**Refer to ICAO-IATA Dangerous Goods Regulations.**

Sizes 1 L and under  
**Limited Quantity**

Max Net Qty/Pkg  
30 kg G



*FOR REFERENCE ONLY*

**UN number:** UN1950

**Shipping Name:** AEROSOL, non-flammable

**Class:** 2.2

**Packing Group:** Not applicable

**Marine Pollutant:** No

**Sea**

**Refer to IMDG regulations.**

Sizes 1 L and under  
**Limited Quantity**



*FOR REFERENCE ONLY*

**UN number:** UN1950

**Shipping Name:** AEROSOL, non-flammable

**Class:** 2.2

**Packing Group:** Not applicable

**Marine Pollutant:** No

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**826****STATIC OFF™ ANTISTATIC FOAMING SPRAY****Section 15: Regulatory Information****Canada****Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**


All hazardous ingredients are listed on the DSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

**USA****Other Classifications****HMIS® RATING**

<b>HEALTH:</b>	<b>2</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**

*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains up to 3% propan-2-ol (CAS # 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

*Section continued on the next page*

**826****STATIC OFF™ ANTISTATIC FOAMING SPRAY****TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>Prepared by the</b>	Regulatory Affairs Department
<b>Date of Review</b>	28 February 2020
<b>Supersedes</b>	06 May 2019
<b>Reason for Changes:</b>	Update to the emergency phone number information.

**Reference**

- 1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

*Section continued on the next page*

**826****STATIC OFF™ ANTISTATIC FOAMING SPRAY****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
ECHA	European Chemicals Agency
EU	European Union
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

Phone: +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer**

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.