



NOTES:

1. MATERIAL: 0.30/(.012) THICK BRASS
2. FINISH: HOT TIN DIP, 0.00051/(.000020) MIN.
3. PRODUCT SPECIFICATION: PS-43374-001
4. DIMENSIONS FOR REFERENCE ONLY.
5. NO PORTION OF THE LOCK TANG BEAM SHALL TOUCH ANY PORTION OF THE OTHER LOCK TANG BEAM.
6. SINGLE CRIMP TO 22-24 AWG WIRE, UL 1007/1569 INSULATION.

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										
	DIMENSION UNITS	SCALE	CURRENT REV DESC: RELEASED								
$\frac{F}{A} = 0$	MM/INCH	10:1	EC NO: 662027								
$\frac{E}{C} = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: MKIPPER 2021/04/26							433747001-SD	
$\frac{E}{P} = 0$	ANGULAR TOL $\pm 0.5^\circ$		CHK'D: SSOUSEK 2021/05/05							DOC TYPE DOC PART REVISION	
DIVISIONAL SYMBOLS	4 PLACES \pm		APPR: FSMITH 2021/05/10							PSD 000 A	
	3 PLACES \pm		INITIAL REVISION:							MATERIAL NUMBER	
	2 PLACES ± 0.25		DRWN: MKIPPER 2021/04/26							CUSTOMER	
1 PLACE ± 0.35		APPR: FSMITH 2021/05/10							GENERAL MARKET		
0 PLACES \pm		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING	SERIES	SHEET NUMBER			
				C-SIZE	43374	43374-7001		1 OF 1			