

Würth Elektronik eiSos GmbH & Co. KG

EMC & Inductive Solutions

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany

Tel. +49 (0) 79 42 945-0 · Fax +49 (0) 79 42 945-400

eiSos@we-online.de · www.we-online.de



Product / Process Change Notification (PCN)

- Major change
 Minor change

PCN #:	PCN_AbsDSubMon_20200922_1	Change Category:	<input type="checkbox"/> Equipment / Location
Affected Series:	WE-D-SUB Plastic Connector Housing; 26xxx		<input checked="" type="checkbox"/> General Data
PCN Date:	June 22, 2020		<input type="checkbox"/> Material
Effective Date:	September 22, 2020		<input type="checkbox"/> Process
			<input type="checkbox"/> Product Design
			<input type="checkbox"/> Shipping / Packaging
			<input type="checkbox"/> Supplier
			<input type="checkbox"/> Software

Contact:	Product Management	Data Sheet Change:	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No
Phone:	+49 (0) 7942 - 945 5001			
Fax:	+49 (0) 7942 - 945 5179	Attachment:	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No
E-Mail:	pcn.eisos@we-online.com			

DESCRIPTION AND PURPOSE OF CHANGE:

In line with internal standardisation, Würth Elektronik will change the data sheet design to new Würth Elektronik design.

This is a datasheet correction only. There will be no change in form, fit, function, quality or reliability of the product.

The following article numbers are affected:

260709	260715	260725
260737	260750	

Würth Elektronik eiSos GmbH & Co. KG

EMC & Inductive Solutions

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany

Tel. +49 (0) 79 42 945-0 · Fax +49 (0) 79 42 945-400

eiSos@we-online.de · www.we-online.de



DETAIL OF CHANGE:

During the data sheet design change following properties will be renamed:

Before Correction	After Correction
Attenuation = 40dB min @ 100MHz	Attenuation: 40dB min @ 100MHz
Operating temperature: -40°C up to +85°C	Operating Temperature: -40 up to +85 °C

Additional information which will be added to the data sheet:

- Number of contacts

RELIABILITY / QUALIFICATION SUMMARY:

There will be no change of the product, therefore no additional reliability or qualification testing will be performed.