

H G F E D C B A



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Without Plating
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours
- Mass : 28.7 g ± 10%

| Connector dimension | |
|---------------------|----------|
| Dim | Nominal |
| ØS | 38.5 Max |
| Z | 31 Max |
| VV THREAD | M28x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D519X11PAL

| | | | |
|---|-------------------------------------|--------------------------------|-------------------------------|
| A | 19-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | | Composite Plug 8D series | |
| SCALE | NA | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| SOURIAU | | WWW.SOURIAU.COM | |
| This document is the property of SOURIAU it must not be reproduced or communicated without permission | | | |
| FORMAT | SOURIAU DRG N° 8D519X11PAL-C | | SHEET 1/2 |

| | | | | | | | | | | |
|----------------|-------------------------|---|---|----|---------------------------------|----|---|---|---|------------------------|
| BASIC SERIES: | 8D | 5 | - | 19 | X | 11 | P | A | L | Delivered W/O Contacts |
| SHELL TYPE : | Plug with RFI Shielding | | | | ORIENTATION : A | | | | | |
| CONTACT TYPE : | Standard Crimp Contact | | | | CONTACT TYPE : PIN(500 Matings) | | | | | |
| SHELL SIZE : | 19 | | | | CONTACT LAYOUT : 19-11 | | | | | |
| PLATING : | X = Without Plating | | | | | | | | | |

H G F E D C B A

Contact Layout



| Contact position ID | Location | | Contact position ID | Location | |
|---------------------|-------------|-------------|---------------------|-------------|-------------|
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +105 (2.67) | +260 (6.60) | G | -275 (6.99) | -053 (1.35) |
| B | +250 (6.35) | +132 (3.35) | H | -250 (6.35) | +132 (3.35) |
| C | +275 (6.99) | -053 (1.35) | J | -105 (2.67) | +260 (6.60) |
| D | +179 (4.55) | -215 (5.46) | K | +000 (0.00) | +105 (2.67) |
| E | +000 (0.00) | -281 (7.14) | L | +000 (0.00) | -092 (2.34) |
| F | -179 (4.55) | -215 (5.46) | --- | --- | --- |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 19 | -11 | 11 | 16 | II | All | MS20054-11 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D519X11PAL

| | | | |
|----------------|-------------------------------------|----------------------------|---|
| A | 19-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Composite Plug 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D519X11PAL-C | | SHEET 2/2 |