




American Opto Plus LED Corp.

L314SYD

3mm Yellow LED Lamp

PACKAGE OUTLINES



Notes:

1. All dimensions are in millimeters (inch).
2. Tolerances are $\pm 0.25\text{mm}$ (± 0.01 inch) unless otherwise noted.

Part Number	Material	Color	
		Emitted	Lens
L314SYD	AllnGaP	Yellow	Yellow Diffused



American Opto Plus LED Corp.

L314SYD

3mm Yellow LED Lamp

ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	72	mW
Reverse Voltage	V_R	5	V
Forward Current	I_F	30	mA
Peak Forward Current (Duty=0.1, 1kHz)	I_{FP}	100	mA
Operating Temperature Range	T_{OPR}	-40~+80	°C
Storage Temperature Range	T_{STG}	-40~+100	°C
Lead Soldering Temperature	T_{SOL}	Max 260°C for 5 sec (1.6mm(0.063inch) from Body)	

OPTICAL-ELECTRICAL CHARACTERISTICS

(Ta=25°C)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V_F	$I_F=10mA$	--	2.0	2.4	V
Dominant Wavelength	λ_D		--	588	--	nm
Viewing Angle	$2\theta_{1/2}$		--	50	--	deg
Luminous Intensity	I_V		--	77	170	--
		$I_F=20mA$	110	250	--	
Reverse Current	I_R	$V_R=5V$	--	--	100	μA

Notes:

1. Forward voltage data did not include $\pm 0.1V$ testing tolerance.
2. Luminous intensity data did not included $\pm 15\%$ testing tolerance.



American Opto Plus LED Corp.

L314SYD

3mm Yellow LED Lamp

BIN COMBINATIONS

Luminous Intensity Rank Limits ($I_F=10\text{mA}$)

Code	Min	Max	Unit
19	77	130	mcd
20	130	170	
21	170	220	
22	220	290	

Dominant Wavelength Rank Limits ($I_F=10\text{mA}$)

Code	Min	Max	Unit
Y6	586.5	588	nm
Y7	588	590	
Y8	590	592	
Y9	592	594	

Forward Voltage Rank Limits ($I_F=10\text{mA}$)

Code	Min	Max	Unit
B	1.6	1.8	V
C	1.8	2.0	
D	2.0	2.2	
E	2.2	2.4	

Notes:

1. Luminous intensity tolerance: $\pm 15\%$
2. Dominant wavelength tolerance: $\pm 2\text{nm}$
3. Forward voltage tolerance: $\pm 0.05\text{V}$
4. One delivery will include several color rank, V_F rank & I_v rank of products. The quantity-ratio of ranks is decided by AOP.



American Opto Plus LED Corp.

L314SYD

3mm Yellow LED Lamp

OPTICAL CHARACTERISTIC CURVES

Fig 1. Forward Current vs. Forward Voltage




Fig 2. Relative Intensity vs. Forward Current




Fig 3. Forward Voltage vs. Temperature




Fig 4. Relative Intensity vs. Temperature




Fig5. Relative Intensity Vs. Wavelength





Fig6. Relative Luminous Intensity Vs. RadRadiation





American Opto Plus LED Corp.

L314SYD


3mm Yellow LED Lamp

PRECAUTION FOR USE

1. Recommended Soldering Condition

1.1 Wave Soldering

Basic spec is ≤ 5 sec. when 260°C . If temperature is higher, time should be shorter ($+10^{\circ}\text{C} \rightarrow -1$ sec).



1.2 Soldering Iron

Power dissipation of iron should be smaller than 15W and temperature should be controllable. Surface temperature of iron tip should be under 230°C , soldering time ≤ 3 sec.

2. Electrostatic Discharge (ESD)

Static electricity or surge voltage will damage the LEDs.

Use of conductive wrist band or anti-electrostatic glove when handling these LEDs is recommended. All devices, equipment, work table, storage rack and machinery must be properly grounded.

In the events of manual working in process, make sure devices are well protected from ESD at all times.