ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00501	Connector, 4C audio plug, 3.5xL20.7 mm, brass, gold plated, molding style	2	
2	30-00495	Wire, 3C TS, 28 AWG, 150V, 70C, 2.8 mm, spiral shield, TPU, WBL	1	Bio-compatible jacket
3	24-00028	Overmold, TPE, black	2	





Wiring Diagram		
50-00501	wire color	50-00501
A	red	A
B	white	B
C	black	C
D	shield	D

Revision:	Date:	Description:
A	10/20/2015	Initial release
A1	11/11/2015	Modified overmold material
A2	01/07/2016	Modified dimensions

Prepared: GL Digitally signed by GL Date: 2018.03.23 16:59:02 -07'00'

Verified: PS Digitally signed by PS Date: 2018.03.27 13:25:35 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Cable, 1830 mm, 3.5 mm 4C 50-00501 slim audio plug to same, 28 AWG, 30-00495, shielded, WBL

TENSILITY

tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A

Part number: 10-02048

Scale: 1:2

Sheet 1 of 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com

5 4 3 2 1