

Feed-through terminal for direct mount, Screw connection, Mounting type: Mounting surface, Rated cross-section: 10 mm<sup>2</sup>, Colour: Beige

### Business data

Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	130.8 g
Weight per piece (including packaging)	134.04 g
Unit of weight	G
Customs number	85369010
Country of origin	DE
Product description	Feed-through terminal for direct mount

---

### Technical data

---

#### Dimensions

---

Length	105.1 mm
Height	31 mm
Hole spacing (mid-point to mid-point)	97.1 mm
Pitch	8 mm

---

#### Ratings

---

Rated voltage	400 V
Rated current	57 A
Rated cross-section	10 mm <sup>2</sup>
Rated impulse voltage	6 kV
Overvoltage category	III
Contamination degree	3
Maximum power dissipation for nominal condition	1.82 W

---

### Technical data

#### Connection data

Connection principle	Screw connection
Connection position	Lateral
Connections	22
Number of terminals per level	2
Number of levels	1
Wire cross-section single-core (rigid) / stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section single core (rigid)/stranded, max.	10 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	10 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	10 mm <sup>2</sup>
Wire cross-section AWG, min.	22
Wire cross-section AWG, max.	8
Stripping length	10 mm
Screw head	Slotted
Screw threading	M 4
Tightening torque, min.	1.2 Nm
Tightening torque, max.	2 Nm

#### Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-2
Working temperature, min.	-40 °C
Working temperature, max.	105 °C

#### Further technical data

Mounting type	Mounting face
Gauge plug acc. to EN 60 947-1	A5
End plate required	✓

#### Print

Colour	Beige
--------	-------

---

### Technical data

---

### Environmental Product Compliance

---

REACH Conform	yes
REACH Reference date	2021-07-08
REACH Candidate Substance Note	No
RoHS Conform	yes

---

# Data sheet

1509.2

BKA 10/11 BG

---

---

### Approvals

---

#### Standards and regulations

---

EAC approval	TR ZU 004/2011
--------------	----------------

---

EAC approval granted	yes
----------------------	-----

---

#### CSA approval

---

CSA approval	C22.2 No 158
--------------	--------------

---

CSA approval granted	yes
----------------------	-----

---

CSA Usegroup C: rated voltage	300 V
-------------------------------	-------

---

CSA Usegroup C: rated current	57 A
-------------------------------	------

---

CSA wire cross-section AWG, min.	22
----------------------------------	----

---

CSA wire cross-section AWG, max.	8
----------------------------------	---

---

CSA stripping length	10 mm
----------------------	-------

---

#### CSAus approval

---

CSAus approval	UL 1059
----------------	---------

---

CSAus approval granted	yes
------------------------	-----

---

CSAus Usegroup C: rated voltage	300 V
---------------------------------	-------

---

CSAus Usegroup C: rated current	57 A
---------------------------------	------

---

CSAus wire cross-section AWG, min.	22
------------------------------------	----

---

CSAus wire cross-section AWG, max.	8
------------------------------------	---

---

CSAus stripping length	10 mm
------------------------	-------

---

---

### Approvals

---

#### KEMA KEUR approval

---


KEMA KEUR approval	EN 60947-7-1:2009
KEMA KEUR approval granted	yes
KEMA rated voltage	400 V
KEMA rated current	57 A
KEMA rated impulse voltage	6 kV
KEMA wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
KEMA wire cross-section single-core (rigid), max.	10 mm <sup>2</sup>
KEMA wire cross-section stranded, min.	0.2 mm <sup>2</sup>
KEMA wire cross-section stranded, max.	10 mm <sup>2</sup>
KEMA torque, min.	1.2 Nm
KEMA torque, max.	2 Nm

---


#### Media



**M4**



**EAC**





---


### Accessories

---

1509.2

BKA 10/11 BG


## Insulated external cross-connector



External insulated cross-connector, No. of poles: 2, Mounting type: Plug in, Width: 16.1 mm, Rated current: 27 A; Colour: Yellow

### General order data


Product number:	Article name	GTIN (EAN)	Packaging unit
2067.0	AQI 2/8/11 YE	4044211048730	500 ST



External insulated cross-connector, No. of poles: 4, Mounting type: Plug in, Width: 32.3 mm, Rated current: 27 A; Colour: Yellow

### General order data

Product number:	Article name	GTIN (EAN)	Packaging unit
2069.0	AQI 4/8/11 YE	4044211048754	500 ST



External insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 24.2 mm, Rated current: 27 A; Colour: Yellow

### General order data


Product number:	Article name	GTIN (EAN)	Packaging unit
2068.0	AQI 3/8/11 YE	4044211048747	500 ST

Creation date 15.11.2021 09:44:45  
Subject to technical changes

1509.2

BKA 10/11 BG

## Quick marking



Terminal marker / Pocket Maxicard, Length: 5 mm, Width: 8 mm, Colour: White

## General order data

Product number:	Article name	GTIN (EAN)	Packaging unit
9323.7	PMC SB 8/40 WH	4044211129231	500 ST

## Screwdriver



Screwdriver with bare blade, Colour: Black-grey

## General order data

Product number:	Article name	GTIN (EAN)	Packaging unit
1087.0	SDB 0,8x4,0	4044211014803	500 ST