

Socket terminal block - JBC 2,5/3 - 3240164

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




3-pos. socket terminal block with spring-cage connection, for toolless wiring with push-in connection method, for one and multi-strand conductors with a cross section of 0.5 to 2.5 mm², insulation housing transparent.

Your advantages

- ✓ Thanks to Push-in connection technology, the three junction box connector versions from Phoenix Contact enable tool-free wiring in a small amount of space
- ✓ Different cross sections can be wired together in a junction box connector
- ✓ Solid multi-strand conductors (7 litz wires) with a cross section range of 1.5 mm² to 2.5 mm² can be safely connected
- ✓ Solid single-strand conductors with a cross section range of 0.5 mm² to 2.5 mm² can be connected
- ✓ The transparent housing makes it easier to carry out a visual inspection of the terminal points, thereby increasing wiring safety
- ✓ Integrated test openings enable the use of test devices once wiring has been completed



Key Commercial Data

Packing unit	100 pc
Minimum order quantity	100 pc
GTIN	 4 046356 457941
GTIN	4046356457941

Technical data

General

Number of positions	3
Number of levels	1
Number of connections	3
Nominal cross section	2.5 mm ²
Color	transparent
Insulating material	PC/PA
Flammability rating according to UL 94	V2
Ambient temperature (operation)	-40 °C ... 90 °C
Maximum load current	24 A

Socket terminal block - JBC 2,5/3 - 3240164

Technical data

General

Nominal current I_N	24 A
Nominal voltage U_N	450 V

Dimensions

Width	17.2 mm
Length	15.6 mm
Height	8.9 mm
Depth	15.6 mm

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	14
Conductor cross section flexible, with ferrule without plastic sleeve min.	0 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	0 mm ²

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals


UL Listed / EAC / EAC


Ex Approvals

Approval details

Socket terminal block - JBC 2,5/3 - 3240164

Approvals

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 327420
Nominal voltage UN		600 V	
Nominal current IN		12 A	
mm ² /AWG/kcmil		20-16	

EAC		7500651.22.01.00246
-----	---	---------------------

EAC		EAC-Zulassung
-----	---	---------------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>