


Copper Conductor  
42/0.16±0.1572mm

Jacket Thickness 1.14mm  
Overall Diameter 3.4\*6.8(±0.2)mm



(Wire Cross-Section)

Plug Component			Plug Strip Dimension			Wire Spec.	Terminal ROJ & Strip			Terminal Component		
Color	Component	Qty	Strip	ROJ	Color	SPT-2 18AWGX2C 105°C BLACK Length: 1829±50 mm	Strip	ROJ	Color	Component	Color	Qty
40P Black 90±5°A	LT-301(10A 125V) (NEMA1-15P)	1	7±1	15±3	Black		6±1	18±3	Black	IEC 320 C7 (LT-503B(7A 125V))	40P BK 90±5°A	1
Nickel-Plated	UL Blades	2	7±1	15±3	Black		6±1	18±3	Black	0 Type terminals	Copper	2

**NOTE :**

1. PLUG : LT-301 AMERICAN TYPE
2. CONNECTOR : NA
3. CORD : SPT-2 18AWGX2C 105D BK 6FT
4. APPROVALS : UL, C-UL
5. Supplier for flexible cord : WU LI
6. Hi-Pot Test:2000v/1min<1mA>

**Marking:**

WU LI : (UL) 105°C SPT-2 VW-1 E94163 2\*0.824mm<sup>2</sup>(18AWG)  
300V WU LI CSA TYPE SPT-2 FT2 105°C LL85694  
2\*0.824mm<sup>2</sup>(18AWG) 300V L.F.

**Modification History**

NO.	DESCRIPTION	DATE

<b>DRAWER</b>	Aaron	<b>DATE</b>	20/10/27	<b>P/N</b>	800-1809-2-SPT2-BL-0006F-1
<b>APPROVE</b>		<b>REV.</b>	0	<b>Dr.No.</b>	10910106
		<b>TOL.</b>	±5mm	<b>ALL DIMENSIONS IN mm</b>	

**CnC Tech**  
Industrial Cable and Connector Technology