



SOLDER PAD POSITION  
焊接PIN位示意图

PIN ASSINGMENT

P1		P2
A4, A9, B4, B9	Red (VBus)	A4, A9, B4, B9
A5	Blue (CC)	A5
A7	White (D-)	A7
A6	Green (D+)	A6
A1, A12, B1, B12	Black (GND)	A1, A12, B1, B12
SHELL	Braid	SHELL

一、Electrical charactor:

- (1) 100% Open & Short Testing
- (2) Withstanding Voltage:DC 300V, 0.01s
- (3) Insulation impedance:  $\geq 10M\Omega$
- (4) Conduction impedance:  $\leq 0.4\Omega$

二、Rated voltage:5V, Current:3A  
Rated voltage:9V, Current:2A

ITEM	PART No.	NAME	DESCRIPTION	Q' TY	UNIT
5	ZTPE-101C60	MOLDED	TPE插頭料, 黑色, 85A (45P), UL94-HB, 符合ROHS+HF	N/A	KG
4	PLASTIC-086	MOLDED	LD-PE, 透明	N/A	KG
3	ZTC01M02SPT1	SHIELD	TYPE C EMI Shell, SUS304, T=0.25mm, 镀镍, (L=13.90*H3.60*W9.00), 带柳爪.	2	PC
2	ZTC22MG024SX01Z0	CONN	TYPE C/M, 24pin, pin针镀金, 黑色胶芯, 外壳镀镍, 一体拉伸式, 超薄款	2	PC
1	C000023L11L-4C	CABLE	USB2.0 30AWG/2C+30AWG/1C+23AWG/1C+F+EAB OD:3.5mmTPE 黑色	1.0	M

MATERIAL SPECIFICATION

SYM	NAME	DATE	REVISIONS	DRAWN BY	CHECKED BY	APPROVED BY	CONFIRMED BY	DESCRIPTION	CUST. CODE	
								TYPE CM TO CM Cable ASSY	CviLux Corporation	
								SHEET: 1 OF 1	DRAWING No.	CUSTOMER P/N
									D000072A	DH-20UE0063-NH



瀚荃股份有限公司  
CviLux Corporation