

Future-Ready Industrial Ethernet Radio

FreeWave's ZumLink™ 900 Series is made for secure collection, transport, and control of data in rugged industrial environments, providing a long-range, low-power solution for remote wireless communications—with capabilities that can be seamlessly added as IIoT requirements evolve.

The ZumLink Z9-PC and Z9-PC-SR001 for OEMs operate in the unlicensed 900 MHz spectrum and utilize Frequency Hopping Spread Spectrum (FHSS) technology for cybersecure data transfer with RF link rates up to 4 Mbps. Performance is further enhanced by FreeWave's Network Accelerators, which utilize techniques such as packet compression, packet aggregation, forward error correction, and Adaptive Spectrum Learning to maximize network throughput, efficiency, and reliability.

ZumLink OEM radios are ideal for integration in networks, systems, and devices used by oil and gas, precision agriculture, water / wastewater, smart cities, and utilities. They provide a Cost, Size, Weight, and Power (CSWaP) advantage with their small, lightweight form factor, industry-leading low power consumption, and low-cost integration. Conformal coating is available for applications with salt spray, moisture, dust, or corrosion concerns.

The ZumLink 900 Series is also software upgradable to include FreeWave's IQ Application Environment, a Linux-based operating system for developing and deploying third-party applications.

Key Features

Operates in the Unlicensed 900 MHz Spectrum: Cost-effective, easy to deploy

High Speed Data Rates: Five RF link rates supporting from 80 kbps to 4 Mbps

Long Range: Up to 97 km (60 miles) with clear line of sight

Safe for Hazardous Locations: Class I, Division 2 certified to board level

Leverages FreeWave's Network Accelerators: to maximize network efficiency

- **Packet Compression:** Minimizes packet transmission
- **Packet Aggregation:** Increases throughput
- **Forward Error Correction:** Improves network reliability
- **Adaptive Spectrum Learning:** Reduces the impact of interferences

Low Current Consumption: 330 mA @ 12 V in transmit; 108 mA @ 12 V in receive

Secure: SSH, SNMP, 128- and 256-bit AES counter mode encryption

Reliable Communication: CRC, ARQ, FEC

CSWaP Advantage: Optimal Cost, Size, Weight, and Power combination

Upgradable with the IQ Application Environment: Linux-based operating system and storage for applications built in any Linux-compatible language

Transmitter

| | |
|-------------------------|--|
| Frequency Range* | 902 to 928 MHz |
| Output Power* | 10 mW to 1 W; user selectable |
| Range | 97 km (60 miles) with clear line of sight |
| Channel Spacing | 230.4, 345.6, 691.2, 1382.4, 1612.8 (Beta), 3225.6 kHz |
| RF Data Rate | 115.2, 250, 500 kbps, 1, 1.5 (Beta), & 4 Mbps; user selectable |

Receiver

| | | | |
|-----------------------|----------------------|--------------------|-----------------|
| IF Selectivity | > 40 dB | | |
| System Gain | 135 dB | | |
| Sensitivity | RF Data Rates | Without FEC | With FEC |
| | 115.2 kbps | -105 dBm | -108 dBm |
| | 250 kbps | -102 dBm | -105 dBm |
| | 500 kbps | -99 dBm | -102 dBm |
| | 1 Mbps | -95 dBm | -98 dBm |
| | 1.5 Mbps (Beta) | -90 dBm | -93 dBm |
| | 4 Mbps | -83 dBm | -86 dBm |

Data Transmission

| | |
|-----------------------------|---|
| Type | Frequency Hopping Spread Spectrum |
| Modulation | 2 level GFSK 4- and 8-ary FSK |
| Link Throughput | Up to 1.6 Mbps; 4 Mbps with Compression |
| Error Detection | ARQ and CRC, retransmit on error, FEC |
| Hopping Rates | 400, 200, 100, 50, 25 ms |
| Hopping Channels* | Up to 112; RF Data Rate Dependent |
| Hopping Patterns | Up to 16; RF Data Rate Dependent |
| Protocol | Adaptive Spectrum Learning (ASL) |
| User Interface Rates | Ethernet Rate: 10/100 Mbps Serial Rate: up to 250 kbps |
| Data Encryption | 128-bit and 256-bit AES CCM |
| Advanced Features | Packet Compression and Aggregation |

Computing Resources (OPTIONAL UPGRADE)**

| | |
|----------------|---------------------|
| CPU | ARM Cortex-A8 1 GHz |
| RAM | 512 MB |
| Storage | 1 GB |
| OS | Debian-based Linux |

Management

| | |
|-------------------|--|
| Management | HTTP, SSH SNMPv1/v2c/v3, Enterprise MIB, Modbus |
|-------------------|--|

Networking

| | |
|--------------------------|--|
| VLAN | 802.1Q |
| Serial | TCP server, Modbus/TCP, Modbus RTU, TCP client |
| Traffic Filtering | Netmask filter, ARP filter |


Interfaces

| | |
|------------------------|--|
| Data Connectors | Dual Row 10-pin header 1 Ethernet / Power, 2 Serial |
| USB Connector | Micro USB |
| RF Connector | MMCX |

Power Requirements

| | | | | |
|----------------------------|----------------|-----------------|----------------|-------------|
| Operating Voltage | +5 to +12 VDC | | | |
| Current Consumption | Voltage | Transmit | Receive | Idle |
| | 12 VDC | 330 mA | 108 mA | 91 mA |

General Information

| | |
|------------------------------|--|
| Operating Temperature | -40°C to +85°C (-40°F to +185°F) |
| Humidity | 0 to 95%, non-condensing |
| Dimensions | Z9-PC: 101.60 L x 50.80 W x 12.45 H (mm) 4.0 L x 2.0 W x 0.49 H (in) Z9-PC-SR001: 101.60 L x 50.80 W x 16.51 H (mm) 4.0 L x 2.0 W x 0.65 H (in) |
| Weight | Z9-PC: 41 g (0.09 lbs) Z9-PC-SR001: 45 g (0.10 lbs) |
| Reliability | MTBF 207,801 |
| Safety | Class I, Division 2, Groups A-D |
| UL |  |
| RoHS | Directive 2011/65/EU |

Information to Order

| Model Number | Description |
|-----------------------|--|
| Z9-PC | Board Level Unit, 902 to 928 MHz |
| Z9-PC-SR001 | Board Level Unit with RJ-45, 902 to 928 MHz |
| Z9-PC-DEVKIT | Includes 2 Z9-PC units and accessories |
| Z9-PC-CC | Board Level Unit, 902 to 928 MHz, Conformal Coating |
| Z9-PC-SR001-CC | Board Level Unit with RJ-45, 902 to 928 MHz, Conformal Coating |

*Country-specific models and information are available. Contact FreeWave Sales for information. | **Requires licensing. Contact FreeWave Sales for information.