

Specification Sheet

Part Number: 596-00826

⚠ ADVERTENCIA:
CONEXIÓN DE SALIDA DEL INVERSOR.
NO REUBICAR ESTE DISPOSITIVO DE SOBRECARGA.

Solar Label, Spanish, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 4.12" x .75",
VL,Orange,50/roll

Article Number

596-00826

Type

IOCODS

Color

Orange (OG)

Features & Benefits

- Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.
- Supplied with an aggressive adhesive to ensure long life.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
- Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

Quantity Per

roll

Product Description

HellermannTyton pre-printed vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Spanish, WARNING INVERTER OUTPUT...OVERCURRENT DEVICE, 4.12" x .75", VL,Orange,50/roll

Global Part Name

IOCODS-443/552-OG

Technical Description

Pre-Printed Solar Label, Spanish Version, "INVERTER OUTPUT CONNECTION", 4.125" X .75", Orange

Local Order Number 2

English Version: 596-00589

Width W (Imperial)

4.125

Width W (Metric)

104.6

Thickness T (Metric)

64.0

Height H (Imperial)

0.75

Height H (Metric)

19.05

Material

Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate

Material Shortcut

443/552

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	UL 969
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521
Weight (Imperial)	3.2

