

PRODUCT CHANGE NOTIFICATION

#PCN-TT-R6KG-16

Business Unit	Product Line Code	Type of Change	Action	Date of issue
TT	CL3	Electrical	Notify Distributors and Field	4/11/2016

The following Phoenix Contact products have been modified. Existing specifications will be met or exceeded. Please review and acknowledge this document and inform your personnel as needed.

Description of Change:

The following products have been reevaluated to the new IEC 61643-21 standard and the technical data has been updated to reflect this change. See the attached chart to view the change in maximum continuous voltage, AC nominal current, and DC nominal current values. There were no technical changes to the products.

Warranty Information:

N/A

Stock Status

Can existing stock still be used? Y

Is mixture of stock acceptable? Y

Transaction Dates:

Date modification goes into effect from Germany: 4/11/2016

Expected first shipment (from Phoenix Contact) of the modified product(s):

PRODUCT CHANGE NOTIFICATION

Should you have any issues with the timeline or content of this change, please contact Phoenix Contact using the contact information below. Customers should acknowledge receipt of the PCN within 30 days of delivery of the PCN; provided, however that the failure to acknowledge receipt does not affect the product change or the effective date thereof.

Contact Info:

Jack Coghlan
jcoghlan@phoenixcon.com
(717) 944-1300 x3531

Thank you,



Surge and Overcurrent Protection, Product Marketing Manager

Part#	Type Description
2838526	CTM 2X1-110AC
2838568	CTM 1X2- 60DC
2838542	CTM 2X1- 60DC
2838539	CTM 1X2-110AC

PRODUCT CHANGE NOTIFICATION

	old	new
CTM 2X1-110AC, 2838526		
Maximum continuous voltage U_C	180 V DC	60 V DC
Nominal current I_N (DC value added)	-	150 mA DC
Nominal current I_N (AC value added)	380 mA	380 mA AC
CTM 1X2-110AC, 2838539		
Maximum continuous voltage U_C	180 V DC	60 V DC
Nominal current I_N (DC value added)	-	150 mA DC
Nominal current I_N (AC value added)	380 mA	380 mA AC
CTM 2X1- 60DC, 2838542		
Maximum continuous voltage U_C	65 V DC	60 V DC
Nominal current I_N (DC value added)	-	150 mA DC
Nominal current I_N (AC value added)	380 mA	380 mA AC
CTM 1X2- 60DC, 2838568		
Maximum continuous voltage U_C	65 V DC	60 V DC
Nominal current I_N (DC value added)	-	150 mA DC
Nominal current I_N (AC value added)	380 mA	380 mA AC