

## SUMMARY

### # Wires

Low voltage	10
Fluidic	1

*Image is for illustrative purpose only*

Series	2P
Termination type	Female solder
IP rating	66
AWG wire size	30.00 - 22.00
Cable Ø	0.00 - 0.00 mm
Status	active
Matching parts	<a href="#">CFB.P15.GLA.C72GZ</a>

### Download

[Request a quote](#)  
[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model	*:
Keying	No keying
Housing Material	PSU (Polysulfone), gray
Weight	5.22 g

### Performance

Configuration	2P.P15 : 1 Fluidic with valve, 10 Low V.
Insulator	L: PEEK for solder contacts
Rated Current	6 Amps

### Specifications

Test voltage (kV rms) Contact-contact: 1.15  
Air clearance min.: 0.9 mm  
Creepage distance min.: 0.9 mm


### Others

Endurance (Shell): >1000 mating cycles  
Temp (min / max): -50°C / +150°C

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*

---

## DRAWINGS



**No keying**

---

## RECOMMENDED BY LEMO

### Tools

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*