

For compatibility with the latest operating systems, please update to the latest firmware, which may be found by clicking the Model Support tab at the bottom of this page.

USB-C to Serial DB9 RS232 Adapter Cable - 3 ft. (0.91 m) Keyspan, High-Speed (M/M), TAA

MODEL NUMBER: USA-19HS-C



USB-C to DB9 adapter connects legacy serial devices, such as lab equipment and digital cameras, to your computer or laptop's USB-C port.

Features

USB-C to Serial Adapter for Use with All RS-232 Serial Devices This Keyspan® adapter lets you connect a legacy DB9/RS-232 serial device to the USB-C port on your computer, laptop, tablet, Chromebook or MacBook. It works with switches, routers, modems, barcode scanners, GPS units, digital cameras, point-of-sale devices, lab equipment, network storage devices and other devices with a 9-pin serial port.

Ready to Begin Transferring Data Almost Immediately The included 3-ft. (0.91 m) detachable cable supports data transfer rates up to 230 Kbps, which doubles the speed of built-in PC serial ports. The USB-C to DB9 adapter also works with any USB-C cable up to 16 feet. LEDs on the unit indicate status and data activity. No external power is needed. The unit weighs just two ounces and is easy to carry in a pocket, purse, backpack or laptop bag for instant file transfers where needed.

Compatible with Major Operating Systems This USB-C to serial adapter works with Windows (up to 11), Mac OS X (up to Ventura 13.3.1) applications. It's easy to upgrade via free software downloads. Windows line monitor and data trace software are included. Supports both 32-bit and 64-bit systems. The driver for newest operating systems are available for download on the Technical Support page.

TAA-Compliant for GSA Schedule Purchases The USA-19HS-C is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Highlights

- Provides full modem control and hardware/software flow control
- Supports data transfer speeds up to 230 Kbps—double the speed of a PC serial port
- Works with any USB-C cable up to 16-ft. (4.88 m) long (detachable 3-ft. (0.91 m) cable is included)
- Works with Microsoft Windows (up to Windows 11) and Mac OS X (up to Mac OS Ventura 13.3.1)
- Small enough to carry in a pocket or purse for fast file transfers anywhere
- Supports 32-bit and 64-bit systems

Applications

- Use a barcode scanner to maintain an accurate inventory on your MacBook drive
- Upload family vacation photos/videos from a digital camera or camcorder to your PC hard drive
- Download a planned route to your GPS device
- Connect a digital signage device to advertise an in-store sale or announcement

System Requirements

- Compatible up to Windows 11 and Windows Server 2016
- Compatible up to Mac OS Ventura 13.3.1

Package Includes

- USA-19HS-C USB-C to Serial Adapter (DB9)
- USB-C cable, 3-ft. (0.91 m)
- CD with driver software and owner's manual

Specifications

OVERVIEW	
UPC Code	037332210753

Device Compatibility	Chromebook; Computer; Laptop; Scanner
Technology	USB
Country/Region	Global
INPUT	
Bus Powered	No
PHYSICAL	
Color	Black
Cable Jacket Color	Black
Shipping Dimensions (hwd / in.)	2.90 x 9.30 x 5.70
Shipping Dimensions (hwd / cm)	7.37 x 23.62 x 14.48
Shipping Weight (lbs.)	0.35
Shipping Weight (kg)	0.16
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
Unit Dimensions (hwd / cm)	2.54 x 4.06 x 7.87
CONNECTIONS	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	DB9 (MALE)
FEATURES & SPECIFICATIONS	
UASP Support	No
Auto MDIX Support	No
Full Duplex Support	No
Suspend Mode Support	No
Remote Wakeup Support	No
Driver Required	No
STANDARDS & COMPLIANCE	
Product Certifications	ICES (Canada); NOM (Mexico)
Product Compliance	Trade Agreements Act (TAA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty



1000 Eaton Boulevard
Cleveland, OH 44122
United States



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.