

LINEAR TECHNOLOGY MATERIALS DECLARATION

1t1529cq-5#pbf

(Engineering Calculation)

DDPAK

(printed on: 2020-07-11 20:11:57)

TOTAL MASS (g) : 1.398938

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|---------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.004380 | 1000000 | 3130.94580078 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.852419 | 998500 | 609332.875 | | |
| | | Iron (Fe) | 7439-89-6 | 0.000000 | 0 | 0 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000000 | 0 | 0 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000000 | 0 | 0 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.001281 | 1500 | 915.694458008 | | |
| Lead Frame Total: | | | | 0.853700 | 1000000 | 610248.5625 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.009978 | 1000000 | 7132.70849609 | | |
| | | External Plating Total: | | | | 0.009978 | 1000000 | 7132.70849609 |
| | | Inter. Plating Ni | 7440-02-0 | 0.004000 | 740740.75 | 2859.31152344 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.001400 | 259259.265625 | 1000.75897217 | | |
| Internal Plating Total: | | | | 0.005400 | 1000000 | 3860.07055664 | | |
| Die Attach | 95Pb / 5 Sn | Silver (Ag) | 7440-22-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000105 | 50000 | 75.0569229126 | | |
| | | Lead (Pb) | 7439-92-1 | 0.001987 | 950000 | 1420.36291504 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000000 | 0 | 0 | | |
| Die Attach Total: | | | | 0.002092 | 1000000 | 1495.42004395 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.053704 | 103000 | 38389.1171875 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.466653 | 895000 | 333576.5625 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.001043 | 2000 | 745.565490723 | | |
| | | Encapsulation Total: | | | | 0.521400 | 1000000 | 372711.25 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.001988 | 1000000 | 1421.07775879 | | |
| | | | | | TOTAL MASS (g) : | 1.398938 | | |