



Click [here](#) for the 3D model.

Dimensions

| | |
|-----------|--|
| Chip Size | 1825 |
| L | 4.57mm +/-0.38mm (0.18 in +/-0.015 in) |
| W | 6.35mm +/-0.38mm (0.25 in +/-0.015 in) |
| T | 2.03mm MAX (0.08 in MAX) |
| B | 0.51mm +/-0.25mm (0.02 in +/-0.01 in) |

Packaging Specifications

| | |
|-----------|-----------|
| Packaging | Bulk, Bag |
|-----------|-----------|

General Information

| | |
|-------------------------|--|
| Series | GR900 SMD Space |
| Style | SMD Chip |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov . |
| SCIP Number | 01642942-375f-41b6-87dc-aef6906a9224 |
| Termination | Lead (SnPb) |
| Failure Rate | N/A |
| Testing and Reliability | GR900 CSAM A |
| AEC-Q200 | No |
| Shelf Life | 78 Weeks |
| MSL | 1 |

Specifications

| | |
|-------------------------|------------|
| Capacitance | 0.033 uF |
| Capacitance Tolerance | 10% |
| Voltage DC | 200 VDC |
| Temperature Range | -55/+125°C |
| Temperature Coefficient | BX |