



Click [here](#) for the 3D model.

Dimensions	
D	76.6mm +/-1mm
L	146mm +/-1mm
T	3.8mm NOM
S	32mm +/-0.5mm
F	15mm +/-0.5mm
DT	15mm NOM
G	13mm NOM
LT	153mm +/-1mm
Z	13mm NOM

Packaging Specifications	
Sleeving	Yes
Packaging	Bulk, Bag
Packaging Quantity	9

General Information	
Series	PEH169
Dielectric	Aluminum Electrolytic
Description	Screw Terminal, Aluminum Electrolytic
RoHS	Yes
Mounting	Stud
AEC-Q200	No
Halogen Free	Yes
Component Weight	800 g
Notes	Dimensions D And L Include Sleeving. M5. MS = M12x16.
Shelf Life	156 Weeks

Specifications	
Capacitance	33,000 uF
Capacitance Tolerance	20%
Voltage DC	100 VDC
Temperature Range	-40/+85°C
Rated Temperature	85°C
Life	28000 Hrs (Rated Voltage And Ripple Current At 85C)
Resistance	6 mOhms (100Hz 20C), 5 mOhms (100kHz 20C)
Ripple Current	28.5 Amps (100Hz 85C), 71 Amps (10kHz 50C), 55.2 Amps (10kHz 40C)
Leakage Current	13900 uA (5min 20°C)
Inductance	17 nH (ESL)