

## Specification Sheet

Part Number: 133-03179

Pipe clip secures routing to panel using a stud mount suited for a 5 or 6mm stud or bolt  
Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure

Inverted retaining legs and narrow opening prevent inadvertent disengagement

Controlled flex and angled entry promote easy installation



Tube and Pipe Clip with 5mm/6mm Stud Mount, 4.7-5.1mm Diameter, PA66HIRHSUV, Black, 5000/carton

**Article Number** 133-03179

**Type** PC5SM6

**Color** Black (BK)

**Quantity Per** carton

**Product Description** These clips can be attached to the stud prior to installing the pipe or hose. The parts prefixed with an 'I' can be interlocked together giving a greater choice of installation options or mounted onto a 5 mm 'T' stud or the IAHC type of Automatic Harness Clips.

**Short Description** Tube and Pipe Clip with 5mm/6mm Stud Mount, 4.7-5.1mm Diameter, PA66HIRHSUV, Black, 5000/carton

|  |  |
|--|--|
| <b>Global Part Name</b>                  | PC5SM6-PA66HIRHSUV-BK  |
| <b>Length L (Imperial)</b>               | 0.39   |
| <b>Length L (Metric)</b>                 | 10.0   |
| <b>Fixation Method</b>                   | Stud Mount   |
| <b>Width W (Imperial)</b>                | 0.58   |
| <b>Width W (Metric)</b>                  | 14.73  |
| <b>Height H (Imperial)</b>               | 0.59   |
| <b>Height H (Metric)</b>                 | 15.1   |
| <b>Nominal Diameter (Metric)</b>         | 4.7  |
| <b>Mounting Hole Diameter D (Metric)</b> | M6   |
| <b>Stud Diameter (Metric)</b>            | M6   |
| <b>Material</b>                          | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| <b>Material Shortcut</b>                 | PA66HIRHSUV  |
| <b>Flammability</b>                      | UL 94 HB   |

**Operating Temperature** -40°F to +230°F (-40°C to +110°C)

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 2000

**Package Quantity (Metric)** 2000

**Customs Number** 3926909988