



8622 Staticide® Flux Remover Lead-Free

For High-Temp, Lead-Free Flux Removal

This powerful solvent removes heavy and encrusted flux deposits resulting from high temperature lead-free soldering applications. This extra-strength cleaner quickly removes all types of flux, oxide particles, carbon, dust, grease, and oil. It evaporates quickly, leaving no residues.

Ideal for the following applications:

- General industrial
- Electronics manufacturing and assembly
- Military defense

FEATURES:

- ❖ Highly effective on the most difficult-to-remove, lead-free products
- ❖ Best for removing heat-degraded flux
- ❖ Superior cleaning strength; surpasses general purpose contact cleaners
- ❖ Flammable
- ❖ Dissolves oil, grease, ionic, and non-ionic residues
- ❖ Evaporates quickly; non-residual


Directions:

To use, spray surface from a distance of 4-6 inches. Apply cleaner from top to bottom, allowing the liquid to flush away flux residues, rosin, oil, and grease. Special valve allows for 360° spraying.

For industrial use only. Read SDS carefully prior to use.

Material Compatibility:

ABS	Poor
Buna-N	Poor
EPDM	Good
Graphite	Good
HDPE	Good
Kynar™	Good
LDPE	Fair
Lexan™	Poor
Neoprene	Fair
Noryl	Poor
Nylon™ 66	Good
Cross-linked PE	Good
Polypropylene	Good
Polystyrene	Poor
PVC	Poor
Silicone Rubber	Poor
Teflon™	Good
Viton™	Poor



Product# 8622

11 oz (312g) aerosol / 12 per case

