



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 41mm -0.7mm     |
| H  | 38mm -0.7mm     |
| T  | 21mm -0.7mm     |
| S  | 37.5mm +/-0.5mm |
| LL | 4mm +2mm        |
| F  | 1mm +/-0.05mm   |
| G  | 0.5mm NOM       |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | Pizza, Box |
| Packaging Quantity | 105        |

### General Information

|                  |   |
|------------------|---|
| Series           | F461  |
| Dielectric       | Metallized Polypropylene  |
| Style            | Radial  |
| Features         | MKP, Pulse  |
| RoHS             | Yes   |
| Lead             | Cut/Short   |
| AEC-Q200         | No  |
| Component Weight | 34.4 g  |
| Miscellaneous    | The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56. |
| Notes            | Series Replaced by R75.   |

### Specifications

|                       |                        |
|-----------------------|------------------------|
| Capacitance           | 27 uF                  |
| Capacitance Tolerance | 10%                    |
| Voltage AC            | 90 VAC                 |
| Voltage DC            | 160 VDC, 96 VDC (105C) |
| Temperature Range     | -55/+105°C             |
| Rated Temperature     | 85°C                   |
| Dissipation Factor    | 0.1% 1kHz              |
| Insulation Resistance | 1.111 GOhms            |
| Max dV/dt             | 35 V/us                |
| Inductance            | 6 nH                   |