



Click [here](#) for the 3D model.

Dimensions

| | |
|----|---------------|
| D | 36.6mm +/-1mm |
| L | 51.5mm +/-1mm |
| T | 4.4mm NOM |
| S | 13mm +/-0.5mm |
| F | 8mm +/-0.5mm |
| DT | 8mm NOM |
| LT | 58.9mm +/-1mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Sleeving | Yes |
| Packaging | Bulk, Bag |
| Packaging Quantity | 42 |

General Information

| | |
|------------------|--|
| Series | PEH169 |
| Dielectric | Aluminum Electrolytic |
| Description | Screw Terminal, Aluminum Electrolytic |
| RoHS | Yes |
| Mounting | Stud |
| AEC-Q200 | No |
| Halogen Free | Yes |
| Component Weight | 70 g |
| Notes | Dimensions D And L Include Sleeving. M5. MS = M8x12. |
| Shelf Life | 156 Weeks |

Specifications

| | |
|-----------------------|--|
| Capacitance | 3,300 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 63 VDC |
| Temperature Range | -40/+85°C |
| Rated Temperature | 85°C |
| Life | 14000 Hrs (Rated Voltage And Ripple Current At 85C) |
| Resistance | 30 mOhms (100Hz 20C), 15 mOhms (100kHz 20C) |
| Ripple Current | 7.1 Amps (100Hz 85C), 31.1 Amps (10kHz 50C), 19.4 Amps (10kHz 40C) |
| Leakage Current | 4623.7 uA (5min 20°C) |
| Inductance | 12 nH (ESL) |