

R75PC2150Z340K

Aliases (75PC2150Z340K)

R75, Film, Metallized Polypropylene, General Purpose, 0.015 uF, 10%, 630 VDC, 85°C, Lead Spacing = 5mm



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-------------------|
| L | 7.2mm +0.3/-0.5mm |
| H | 13mm +0.1/-0.5mm |
| T | 7.2mm +0.1/-0.5mm |
| S | 5mm +/-0.4mm |
| LL | 17mm +1/-2mm |
| F | 0.5mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|------|
| Packaging | Bulk |
| Packaging Quantity | 750 |

General Information

| | |
|------------------|---|
| Series | R75 |
| Dielectric | Metallized Polypropylene |
| Style | Radial |
| Features | Automotive Grade, Pulse |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Component Weight | 1.861g |
| Miscellaneous | Above 85C DC voltage derating is 2%/C and AC voltage derating is 1.25%/C. |

Specifications

| | |
|-----------------------|--|
| Capacitance | 0.015 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 220 VAC |
| Voltage DC | 630 VDC |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 600 V/us |
| Resistance | 318.3 mOhms (100kHz) |
| Ripple Current | 0.931 Amps (100kHz 85C), 9 Amps (Peak) |
| Inductance | 7 nH |