



| | | | | | | | | | | | | | |
|---|---------------------------|--|------|-------------------|--------------------|-----------------|-------------------|-------------------------------|------|-----------------|------|----------------|------|
| Number of contacts | Standard | 3 | 4 | 5 | 5 | 6 | 7 | 7 | 8 | 12 | 14 | 14 | 19 |
| Contact arrangement | IEC 61076-2-106 | 03-a | 04-a | 05-a | 05-b | 06-a | 07-a | 07-b | 08-a | 12-a | 14-a | 14-b | 19-a |
| Contact arrangement | IEC 60130-9 ¹⁾ | yes | | no | yes | | no | yes | | no | | | |
| Rated voltage ²⁾ | IEC 60664-1 | 300 V (100 V) | | 300 V (63 V) | 100 V (32 V) | 300 V (63 V) | | 100 V (32 V) | | 150 V (32 V) | | 60 V (32 V) | |
| Rated voltage | UL 1977 | 250V | | | | | | | | 60V | | | |
| Rated impulse withstand voltage ²⁾ | IEC 60664-1 | 1500 V (1500 V) | | 1200 V (800 V) | 1500 V (1500 V) | | 1200 V (800 V) | | | | | | |
| Pollution degree ²⁾ | IEC 60664-1 | 1 (2) | | | | | | | | | | | |
| Installation category | IEC 60664-1 | I | | | | | | | | | | | |
| Insulation group | IEC 60664-1 | II, 400 ≤ CTI < 600 | | | | | | | | | | | |
| Current rating | IEC 60512-5-2 UL 1977 | 10A/+40°C | | 7A/+40°C | | | | | | 3A/+40°C | | | |
| Insulation resistance | IEC 60512-3-1 | >10 ¹⁰ Ohm ³⁾ | | | | | | | | | | | |
| Contact resistance | IEC 60512-2-1 | <5mOhm | | | | | | | | | | | |
| Climatic category | IEC 60668-1 | 40 / 100 / 56 | | | | | | | | | | | |
| Temperatur range | IEC 60668-1 | -40°C...+100°C / -40°F...+212°F | | | | | | | | | | | |
| IP degree | IEC 60529 | IP 40 | | | | | | | | | | | |
| Insertion and withdrawal force | IEC 60512-13-2 | 25N | 30N | 35N | 35N | 50N | 55N | 55N | 60N | 50N | 50N | 50N | 60N |
| mechanical operation | IEC 60512-9-1 | Silver ≥500 mating cycles / Gold ≥1000 mating cycles | | | | | | | | | | | |
| housing material | | brass and / or zinc die cast, nickel plated or thermoplast | | | | | | | | | | | |
| dielectric material | | thermoplastic | | | | | | | | | | | |
| contacts | | silver or gold plated | | | | | | | | | | | |
| termination technique | | solder | | | | | | | | | | | |
| wire gauge | | ≤0,5mm ² / 20 AWG | | | | | | ≤0,35mm ² / 22 AWG | | | | | |
| flamability | | UL 94 V0 | | | | | | | | | | | |
| locking system | | metal screw coupling; tightening torque 0,7 - 1,5 Nm | | | | | | | | | | | |

Gewicht (errechnet) / Calc WT: 0,026 kg
 Prüfmaß / Testdimension
 Teileindex / Partindexnumber:
 Bagatelle change:

Zul. Abw./Tolerances:
 ISO 2768-m
 DIN / ISO 13715

Maßstab / Scale: 2:1
 A3
CUSTOMER DRAWING

Gez. 10.12.2020
 Drawn MCARLE
 Status Released
 Gepr. 10.02.2021
 Checked MBERTSCH

Amphenol Tuchel Industrial GmbH

Male cable connector
 for cable diamter 4-6mm
 Blatt/Sheet 1
 1 Bl.

01 202000083 10.12.2020 MCARLE
 Index Änderung/Description Datum/Date Name

Ers. f. / Replacement for:

M HA T 3XXX 013+130+038 U
 Ers. f. / Replacement for:

| | | | |
|---|----------------|--|--------------|
| | 19 (19-a) | Ag | T 3690 013 U |
| | | Au | T 3690 038 U |
| | 14 (14-b) | Ag | T 3670 013 U |
| | | Au | T 3670 038 U |
| | 14 (14-a) | Ag | T 3650 013 U |
| | | Au | T 3650 038 U |
| | 12 (12-a) | Ag | T 3635 013 U |
| | | Au | T 3635 038 U |
| | 8 (08-a) | Ag | T 3504 013 U |
| | | Au | T 3504 038 U |
| | 7 (07-b) | Ag | T 3484 013 U |
| | | Au | T 3484 038 U |
| | 7 (07-a) | Ag | T 3475 013 U |
| | | Au | T 3475 038 U |
| | 6 (6-a) | Ag | T 3400 013 U |
| | | Au | T 3400 038 U |
| | 5 (05-b) | Ag | T 3360 130 U |
| | | Au | T 3356 038 U |
| | 5 (05-a) | Ag | T 3360 013 U |
| | | Au | T 3360 038 U |
| | 4 (04-a) | Ag | T 3300 013 U |
| | | Au | T 3300 038 U |
| | 3 (03-a) | Ag | T 3260 013 U |
| | | Au | T 3260 038 U |
| | 2 (Pin 1+3) | Ag | T 3200 013 U |
| | | Au | T 3200 038 U |
| Contact arrangement View on mating side | | Number of contacts (Contact arrangement acc. DIN EN 61076-2-106) | |
| | | Part number | |

Copying of this document and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of the utility model or design.
 Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten.