

## Coaxial Cable Connector 11\_MMBX-50-2-2/111\_N

### Description

Straight cable plug

Interface standards  
SUHNER-MMBX



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	12.4 GHz

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0007 kg

#### Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	Gold Plating (without Nickel underplating)

### Related Documents

Outline drawing	DOU-00007630
Catalogue drawing	DOU-00007632
Assembly instruction	DOC-0000179377

### Ordering Information

Single package	11_MMBX-50-2-2/111_NE
----------------	-----------------------

### Additional Information

Suitable cables	K_02252_D, ENVIROFLEX_316_D, G_02232_D
-----------------	--