

## Specification Sheet

Part Number: 150-95500



The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.

<b>Article Number</b>	150-95500
<b>Type</b>	TC5FT6S
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton Bundling Clips are designed to provide simple and easy methods for securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties.
<b>Short Description</b>	Bundling Clip with Fir Tree, 1.46" Long, 0.03" - 0.06" Panel Thickness, PA66HIRHS, Bk, 1000/pkg
<b>Global Part Name</b>	TC5FT6S-PA66HIRHS-BK

<b>Length L (Imperial)</b>	1.46
<b>Length L (Metric)</b>	37.0
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.32
<b>Width W (Metric)</b>	8.0
<b>Height H (Imperial)</b>	0.32
<b>Height H (Metric)</b>	8.2
<b>Panel Thickness Min (Imperial)</b>	0.03
<b>Panel Thickness Max (Imperial)</b>	0.06
<b>Panel Thickness Min (Metric)</b>	0.75
<b>Panel Thickness Max (Metric)</b>	1.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.26 - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.4 - 7.1 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.28
<b>Mounting Hole Diameter D Max (Metric)</b>	7.1

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988