


FS(50)-120X120T2900

Aliases (UFSFS0005HT290)

KEMET, FS, Flex Suppressors, Noise Suppression



L

Click [here](#) for the 3D model.

Dimensions

Sheet Size 120x120mm

L 120mm NOM

W 120mm NOM

Dimensions

T 0.05mm NOM

Packaging Specifications

Tape Thickness 0.01mm

Component Weight 5.03 g

General Information

Series FS

Style Sheet

Description Flex Suppressor Flame Retardant Type

Features Flame Retardant Type

RoHS Yes

Qualifications UL94 V-0, UL File No. E176124

Environment RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free

Specifications

Temperature Range -40/+105°C

Permeability 10 u At 10MHz

Effective Frequency 3 GHz to 40GHz

Specific Gravity 4.5 TYP

Thermal Conductivity 1.17 typical

Surface Resistivity 100 MOhm/sq. TYP

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - 98a76881-d47c-4621-8fc5-aa6509fbaa49

© 2006 - 2023 KEMET

Generated 5/18/2023 - 98a76881-d47c-4621-8fc5-aa6509fbaa49

© 2006 - 2023 KEMET