



MSH-1 **X** - **01** - **XX** - **LF**
(A) (B) (C) (D)

- A. Plating Options
- See Plating Options below
- B. Shunt Style
- C. No. of Shunts
- See shunt box below
- D. Lead Free

Plating options	
G	-10µ Gold on Contact Area/ Flash on Tail
T	-Matte Tin all Over

Specifications:
 Current Rating: 3.0 Ampere
 Insulation Resistance: 1000M Ohms Min.
 Dielectric Withstanding: 600V AC
 Contact Resistance: 20M Ohms Max.
 Operation Temperature: -40°C to +105°C
 Max. Process Temperature
 Peak: 260°C up to 20 secs.
 Process: 230°C up to 60 secs.
 Wave: 260°C up to 6 secs.
 Manual Solder: 350°C up to 5 secs.

No. of Shunts	Dim. A
02	.200
03	.300
04	.400
05	.500
06	.600
07	.700
08	.800
09	.900
10	1.000

Materials:
 Contact Material: Phosphor Bronze
 Insulator Material: Nylon 6T

Tails may be clipped to achieve specific dimensions.

Products cut to specific sizes are uncancellable/ nonreturnable.
 Parts are subject to change without notice.



PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Major League Electronics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Major League Electronics IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DRAWN	EOW		01/19/15
CHECKED	GWE		01/19/15
ENG APPR.			
MFG APPR.			
INTERPRET GEOMETRIC TOLERANCING PER:		ADDRESS:	
MATERIAL:		2533 Centennial Blvd.	
FINISH:		Jeffersonville, In 47130	
NEXT ASSY USED ON:		Phone: 812-670-4174	
APPLICATION		Fax: 812-670-4175	
DO NOT SCALE DRAWING		E-Mail: mle@mlelectronics.com	

TITLE: MSH-1 SERIES
 SIZE DWG. NO. **C**
 SCALE: 8:1

REV **B**
 SHEET 1 OF 1