

American Data Link

22AWG 2-Conductor Solid White Cable

Technical Data Sheet



Manufacturer Part Number: 222X-WH-SPEC-NRC
Inspired LED SKU# 3607-B (Bulk, sold by ft.)

Description: 2-Conductor 22 AWG solid bare copper, insulated and jacketed with an overall white sunlight resistant jacket, **with no rip cord**

NEC Rating: CMR and FPLR –NEC Articles 800 and 760

Approvals: c(ETL)us Listed to UL Standards 444 & 1424
Certified to CSA STD C22.2 No. 214+BR
Complies with European Directive 2002/95/EC RoHS
P-MSHA –CFR Title 30 Part 7, Subpart K, Section 7.408

Flame Rating: UL 1666 Riser Flame Test

Application: Communications cable and/or fire alarm powered limited circuit cable used for riser applications

Construction:

| | |
|------------------------------------|-------------------------------------|
| Number of Conductors- | 2 |
| Size and Stranding- | 22AWG (solid) Bare Copper |
| Insulation Material (Nom.)- | 0.010" PVC |
| Color Code- | Black (-), Red (+) |
| Jacket Material (Nom.)- | 0.015" White Sunlight Resistant PVC |
| Overall Cable Diameter- | 0.104" |

Print Legend: AMERICAN DATA LINK #222X-WH-NRC 2COND 22AWG CMR/FPLR c(ETL)us
75C SUN RES RoHS P-07-KA090003-MSHA 300V **MADE IN THE USA**

Environmental & Electrical Properties:

| | |
|--|------------------------|
| Temperature Rating- | -20°C to 75°C |
| Operating Voltage (Max)- | 300 V RMS |
| Nom. Capacitance btw Cond @ 1KHz- | 25 pf/ft |
| Nom. DC Resistance per Cond @ 20 C- | 16.14 Ohms per 1000 ft |

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond ADL control, all recommendations or suggestions are presented without guarantee or responsibility on our part. ADL and their distributors disclaim all liability in connection with the use of information contained herein or otherwise.

Distributed by
inspired LED



inspiredled.com



orders@inspiredled.com



(480) 941-4286