

## C4BTFBX5350ZANJ

C4BT, Film, Metallized Polypropylene, Power, 35 uF, 5%, 250 VAC, 400 VDC, 70°C, Lead Spacing = 41mm



Click [here](#) for the 3D model.

### Dimensions

L	57.5mm +1.2/-0.7mm
H	50mm +0.3/-0.7mm
T	35mm +0.5/-0.7mm
S	41mm +/-0.2mm
S1	37mm +/-0.2mm
S2	45mm +/-0.2mm
P	25mm NOM

### Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	21

### General Information

Series	C4BT
Dielectric	Metallized Polypropylene
Style	Radial
Features	Switching
RoHS	Yes
Lead	Flat Tabs
AEC-Q200	No
Component Weight	157.1 g
Miscellaneous	KEMET Style A Tabs. Peak Voltage = 600 VDC.

### Specifications

Capacitance	35 uF
Capacitance Tolerance	5%
Voltage AC	250 VAC
Voltage DC	400 VDC
Temperature Range	-40/+85°C
Rated Temperature	70°C
Max dV/dt	34 V/us
Resistance	1.4 mOhms (100kHz)
Ripple Current	52 Amps (100kHz 70C), 1184 Amps (Peak)
Inductance	48 nH