



SIGN	DATE	DESCRIPTION	APPROVER
△	2010.01.30	The material is changed from Brass to Copper	Jacke
△	2010.01.30	The Part No is changed	Jacke
△	07/31/12	Added TUV standard	Chen Bo
△	07/31/12	The Dimension is added	Chen Bo
△	07/31/12	The IEC spec is removed	Chen Bo
△	07/31/12	Soldering temperature changed from 250°C±10°C/5Sec to 260°C± 5°C/5Sec	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item ② Terminal(housing): Thermoplastic (UL94V-0)
 - △ Item ③ Male contact pin: Copper Tin plated
- | | | |
|------------------------------|-------------------------------------|------|
| △ 5 Electrical | cULus | TUV |
| ● Voltage rating: | 300V | 800V |
| ● Current rating: | 20A ¹⁾ 32A ²⁾ | 32A |
| ● Withstanding Voltage: | 1.6KV | 6KV |
| ● Operating temperature: | -40°C to +115°C | |
| △ 6 ● Soldering temperature: | 260°C± 5°C/5 Sec | |
| △ 3 ● Safety Approval: | | |
| ● Critical dimension: | ▽ | |

△ 2 VC xx 02 x 1 xxxx G

Solid Block ———— G RoHS compliant (lead<4%)
 02 2 POLES ———— In copper Alloy
 03 3 POLES

 16 16 POLES

COLOR

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)

000 0 Standard @ Logo
 000 A Standard ANY Logo
 Any special item by customer request, please contact sales department.

DIM		TOL		
		2P-6P	7P-12P	13P-16P
Dim L	(N+2)×7.62	±0.15	±0.20	±0.30
Dim A	N×7.62	±0.15	±0.20	±0.30
Dim B	(N-1)×7.62	±0.15	±0.20	±0.30
Dim C	(N+1)×7.62	±0.15	±0.20	±0.30

ANYTEK		CUSTOMER COPY		ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD				
TITLE		VC 7.62 SERIES (Feed-through header with slip-on connection)						
PART NO.		VCxx02x1xxxxG			DWG NO.		8VC0005	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance		
		Chen Bo 07/31/12	Chen Bo 07/31/12			X. ±0.50		
						X.X ±0.30		
						X.XX ±0.10		
						X° ±1°		
				SHEET: 01/01		REV.: D		