



**SS** Stainless Steel

**4 Type**

- A** Mounting from the back (tapped blind hole)
- B** Mounting from the operator's side

**Specification**



- Stainless steel
  - Type A: European Standard No. 1.4301 (AISI 304)
  - Type B: fine die-cast European Standard No. 1.4308 (AISI CF-8)
  - Matte shot-blasted finish **GS**
  - Slip polished, glossy metallic finish **GP** (only Type A in metric sizes)
- RoHS compliant

**Information**

GN 565.5 cabinet “U” handles are often used in the food industry or other such applications where a non-corrosive material is necessary. The shape of this sturdy handle has good ergonomic features.

Type A cabinet “U” handles are manufactured from a bent aluminum profile. The manufacturing process allows the production of special lengths in relatively small quantities.

see also...

- Cabinet “U” Handles GN 565 (Aluminum)
- Cabinet “U” Handles GN 426.5 (Stainless Steel)
- Cabinet “U” Handles GN 425 (Stainless Steel)
- “Economical” Cabinet “U” Handles GN 728.5 (Stainless Steel, Mounting from the Back or from the Operator's Side)

**On request**

- Special lengths
- Various inch and metric size fasteners and kit packaging

How to order (Inch)	1 Handle width b
	2 Thread d <sub>1</sub>
	3 Length l
	4 Type
	5 Finish
 <p><b>GN 565.5-20-1/4X20-112-A-GS</b></p>	

How to order (Metric)	1 Handle width b
	2 Thread d <sub>1</sub> (Bore d <sub>2</sub> )
	3 Length l
	4 Type
	5 Finish
 <p><b>GN 565.5-20-M6-160-A-GP</b></p>	

### Inch table

Dimensions in: inches - *millimeters*

<sup>1</sup> <b>b</b>	<sup>2</sup> <b>d<sub>1</sub></b> Thread	<sup>3</sup> Length <b>l</b> ±0.01 Type A Shot-blasted <b>GS</b>	<b>a</b>	<b>h<sub>1</sub></b>	<b>h<sub>2</sub></b>	<b>r</b>	<b>t<sub>1</sub></b> min.	<b>t<sub>2</sub></b>
.79 20	1/4 x 20	4.41 112	.51 13	1.93 49	.53 13.5	.51 13	.39 10	.22 5.5
.79 20	1/4 x 20	5.04 128	.51 13	2.01 51	.53 13.5	.51 13	.39 10	.22 5.5
.79 20	1/4 x 20	6.30 160	.51 13	2.01 51	.53 13.5	.51 13	.39 10	.22 5.5

### Metric table

Dimensions in: millimeters - *inches*

<sup>1</sup> <b>b</b>	<sup>2</sup> <b>d<sub>1</sub></b> Thread	<sup>2</sup> <b>d<sub>2</sub></b> Bore	<sup>3</sup> Length <b>l</b> ±0.25			<b>a</b>	<b>h<sub>1</sub></b>	<b>h<sub>2</sub></b>	<b>r</b>	<b>t<sub>1</sub></b> min.	<b>t<sub>2</sub></b>
			Type A Shot-blasted <b>GS</b>	Type A Slip polished <b>GP</b>	Type B Shot-blasted <b>GS</b>						
20 .79	M 6	5.4 .21	112 4.41	112 4.41	112 4.41	13 .51	49 1.93	13.5 .53	13 .51	10 .39	5.5 .22
20 .79	M 6	5.4 .21	128 5.04	128 5.04	128 5.04	13 .51	51 2.01	13.5 .53	13 .51	10 .39	5.5 .22
20 .79	M 6	5.4 .21	160 6.30	160 6.30	160 6.30	13 .51	51 2.01	13.5 .53	13 .51	10 .39	5.5 .22
20 .79	M 6	-	200 7.87	200 7.87	-	13 .51	51 2.01	-	13 .51	10 .39	-
20 .79	M 6	-	250 9.84	-	-	13 .51	51 2.01	-	13 .51	10 .39	-
20 .79	M 6	-	300 11.81	-	-	13 .51	51 2.01	-	13 .51	10 .39	-
20 .79	M 6	-	400 15.75	-	-	13 .51	51 2.01	-	13 .51	10 .39	-

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4

