

## Legal and additional information

### About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, cameras, digital appliances, printers, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at [news.samsung.com](http://news.samsung.com)

Copyright © 2016 Samsung Electronics Co., Ltd. All rights reserved.  
Samsung is a registered trademark of Samsung Electronics Co., Ltd.  
Specifications and designs are subject to change without notice. Nonmetric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.  
95, Samsung 2-ro, Giheung-gu  
Yongin-si, Gyeonggi-do, 446-711  
KOREA

[www.samsungled.com](http://www.samsungled.com)

Rev.2 Oct. 2016

**SAMSUNG**



## Samsung LED Module inFlux Linear

Superior light source  
for high flux luminaires  
covering up to 40,000 lm



**SAMSUNG**



# Superior performance for high flux luminaires in Industrial lighting



## Wide lumen flux coverage (up to 40,000lm)

Optimized for industrial lighting applications to replace T8/T5HO



Low bay




High bay

Lamp	3 lamps T8 32W	4 lamps T8 32W	2 lamps T5 54W	3 lamps T5 54W	4 lamps T5 54W	8 lamps T5 54W
Lamp Flux	7,800-8,400	10,400-11,200	8,900-10,000	13,350-15,000	17,800-20,000	35,600-40,000
inFlux Linear	L04 (2ea)	L06 (2ea)	L04 (2ea)	L06 (2ea)	L04 (4ea) L09 (2ea)	L04 (8ea) L09 (4ea)



## Easy thermal management

- Reduced thermal resistance using Samsung's mid-power LED LM301A



Flip chip based LM301A  
5630 Epi-up chip Package

- High performance without MCPCB

Model	Flux	T <sub>c</sub> measured
inFlux_L04	9080 lm, 140 lm/W	62°C (No MCPCB)
F-Series (F562A)	9020 lm, 137 lm/W	78°C (MCPCB)
F-Series (F564A)	8850 lm, 119 lm/W	60°C (MCPCB)


※ Measured at the same fixture




## Better uniformity & cost effective compared to high-power LEDs

- Better line uniformity


'3535' high-power LED based module



'inFlux\_L04' Linear Module



- Deliver higher lm/W & better lm/\$



## inFlux series



inFlux\_L04



inFlux\_L06




inFlux\_L09



inFlux\_S02



inFlux\_S03



inFlux\_S04

Type	Luminous Flux (lm)	Power Consumption (W)	Input Voltage (V)	IF (mA)	I <sub>max</sub> (mA)	Efficacy (lm/W)	CRI Min.	CCT (K)	Beam Angle (°)	Size (mm)	Temperature Range (°C)	Lifetime (hrs)	Certification	Model Name
inFlux_L04	4,190	32.4	23.5	1,380	1,380	129	80	3500	120	560x24x5.9	-20~+50	50,000	ENEC, CE, UL, cUL	SL-B8V3N80L1WW
	4,260					131								SL-B8U3N80L1WW
	4,540					140								SL-B8T3N80L1WW
	4,540					140								SL-B8R3N80L1WW
inFlux_L06	5,680	43.4	45.7	950	950	131	80	3500	120	560x24x5.9	-20~+50	50,000	ENEC, CE, UL, cUL	SL-B8V4N90L1WW
	5,775					133								SL-B8U4N90L1WW
	6,060					140								SL-B8T4N90L1WW
	6,060					140								SL-B8R4N90L1WW
inFlux_L09	8,390	64.7	46.9	1,380	1,380	130	80	3000	120	560x40x5.9	-20~+50	50,000	ENEC, CE, UL, cUL	SL-B8V7N90L1WW
	8,530					132								SL-B8U7N90L1WW
	9,100					141								SL-B8T7N90L1WW
	9,100					141								SL-B8R7N90L1WW
inFlux_S02	2,095	16.1	11.7	1,380	1,380	130	80	3000	120	280x24x5.9	-20~+50	50,000	ENEC, CE, UL, cUL	SL-B8V1N40L1WW
	2,130					132								SL-B8U1N40L1WW
	2,270					141								SL-B8T1N40L1WW
	2,270					141								SL-B8R1N40L1WW
inFlux_S03	2,840	21.7	22.9	950	950	131	80	3500	120	280x24x5.9	-20~+50	50,000	ENEC, CE, UL, cUL	SL-B8V2N70L1WW
	2,885					133								SL-B8U2N70L1WW
	3,030					140								SL-B8T2N70L1WW
	3,030					140								SL-B8R2N70L1WW
inFlux_S04	4,195	32.4	23.5	1,380	1,380	129	80	3000	120	280x40x5.9	-20~+50	50,000	ENEC, CE, UL, cUL	SL-B8V4N80L1WW
	4,265					132								SL-B8U4N80L1WW
	4,550					140								SL-B8T4N80L1WW
	4,550					140								SL-B8R4N80L1WW

## LED Driver

Power Consumption (W)	Size (mm)	Input Voltage (V)	Output Voltage (V)	Output Current/ch (mA)	Efficiency (%)	THD (%)	Dimming	Certification	Power factor	Remark	Model Name
75	359x30x26.5	120-277	22-52	1,000-2,100	83	<20	0-10V	UL, cUL	>0.9	Output current adjustable by Rset	SI-EPF007040WW
50	300x30x21		20-50	500-1,400							SI-EPF006660WW
75	360x31x26	100-277	27-54	<1,400	>87		Programmable				SI-CA1427501US
100	420x31x26		24-48	<2,000							SI-CA2029601US