

Specification Sheet

Part Number: T30RSF9M4

All-in-one bundling and fastening solution reduces costs and assembly time.

The arrowhead design of these ties offers a low insertion force and a high extraction force.

High-spec materials and superior design deliver versatility, performance and value.



1-Piece Cable Tie/Arrowhead Mount, 6.3"L, 30lb, 0.04"–0.09" Panel Thickness, PA66, Natural, 1000/pkg

Article Number 126-00704

Type T30RSF(U)

Color Natural (NA)

Quantity Per bag

Product Description One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. The arrowhead design of this push mount inserts easily and locks securely in place. HellermannTyton's one-piece mounting ties combine high-specification materials with superior design to deliver dependable performance in a range of applications.

Short Description 1-Piece Cable Tie/Arrowhead Mount, 6.3"L, 30lb, 0.04"–0.09" Panel Thickness, PA66, Natural, 1000/pkg

Global Part Name T30RSF(U)-PA66-NA

Minimum Tensile Strength (Imperial) 30.0

Minimum Tensile Strength (Metric) 135

Length L (Imperial) 6.3

Length L (Metric) 160.02

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14

Width W (Metric) 3.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 1.3

Bundle Diameter Max (Metric) 31.0

| | |
|---|--------------|
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.2 |
| Height H (Imperial) | .20 |
| Height H (Metric) | 5.70 |
| Panel Thickness Min (Imperial) | 0.035 |
| Panel Thickness Max (Imperial) | 0.094 |
| Panel Thickness Min (Metric) | 0.9 |
| Panel Thickness Max (Metric) | 2.4 |
| Mounting Hole Diameter D (Imperial) | 0.19 - 0.22 |
| Mounting Hole Diameter D (Metric) | 4.7 - 5.6 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.19 |
| Mounting Hole Diameter D Max (Imperial) | 0.22 |
| Mounting Hole Diameter D Max (Metric) | 5.6 |

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

| | |
|-------------------------------|----------------------------------|
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL-ZODZ2.E64139 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909988 |