



Illuminated pushbutton, 22 mm, round, plastic with metal front ring, yellow, pushbutton, flat, momentary contact type, with holder, 1NO, LED module with integrated LED 24 V AC/DC, spring-type terminal, with laser labeling, inscription or symbol Customer-specific selection with SIRIUS ACT configurator (CIN)

| | |
|--|--|
| product brand name | SIRIUS ACT |
| product designation | Illuminated pushbuttons |
| design of the product | Complete unit |
| product type designation | 3SU1 |
| product line | Plastic with metal front ring, matt, 22 mm |
| manufacturer's article number | |
| <ul style="list-style-type: none"> • of supplied contact module at position 1 • of supplied LED module • of the supplied holder • of the supplied actuator | 3SU1400-1AA10-3BA0 3SU1401-1BB30-3AA0 3SU1550-0AA10-0AA0 3SU1031-0AB30-0AA0 |
| number of command points | 1 |
| Actuator | |
| design of the actuating element | Button, flat |
| principle of operation of the actuating element | momentary contact type |
| product extension optional light source | Yes |
| color of the actuating element | yellow |
| material of the actuating element | plastic |
| shape of the actuating element | round |
| outer diameter of the actuating element | 29.45 mm |
| marking of the actuating element | Any inscription, text or symbol, can only be ordered via SIRIUS ACT configurator/Configuration Identification Number (CIN) |
| number of contact modules | 1 |
| Front ring | |
| product component front ring | Yes |
| design of the front ring | Standard |
| material of the front ring | Metal, matt |
| color of the front ring | sand gray |
| Holder | |
| material of the holder | Plastic |
| Display | |
| number of LED modules | 1 |
| General technical data | |
| product function positive opening | No |
| product component light source | Yes |
| insulation voltage rated value | 320 V |
| degree of pollution | 3 |
| type of voltage of the operating voltage | AC/DC |
| surge voltage resistance rated value | 4 kV |
| protection class IP | IP66, IP67, IP69(IP69K) |

| | | |
|---|--|---------------|
| <ul style="list-style-type: none"> of the terminal | IP20 | |
| degree of protection NEMA rating | 1, 2, 3, 3R, 4, 4X, 12, 13 | |
| shock resistance | sinusoidal half-wave 15g / 11 ms Category 1, Class B | |
| <ul style="list-style-type: none"> according to IEC 60068-2-27 for railway applications according to EN 61373 | | |
| vibration resistance | 10 ... 500 Hz: 5g Category 1, Class B | |
| <ul style="list-style-type: none"> according to IEC 60068-2-6 for railway applications according to EN 61373 | | |
| operating frequency maximum | 3 600 1/h | |
| mechanical service life (switching cycles) typical | 3 000 000 | |
| electrical endurance (switching cycles) typical | 10 000 000 | |
| thermal current | 10 A | |
| reference code according to IEC 81346-2 | S | |
| continuous current of the C characteristic MCB | 10 A; for a short-circuit current smaller than 400 A | |
| continuous current of the quick DIAZED fuse link | 10 A | |
| continuous current of the DIAZED fuse link gG | 10 A | |
| Substance Prohibitance (Date) | 10/01/2014 | |
| operating voltage | 5 ... 500 V 5 ... 500 V 5 ... 500 V | |
| <ul style="list-style-type: none"> at AC | | |
| <ul style="list-style-type: none"> at 50 Hz rated value at 60 Hz rated value | | |
| <ul style="list-style-type: none"> at DC rated value | | |
| Power Electronics | | |
| contact reliability | One maloperation per 100 million (17 V, 5 mA), one maloperation per 10 million (5 V, 1 mA) | |
| Supply voltage | | |
| type of voltage of the supply voltage of the light source | AC/DC | |
| supply voltage of the light source at AC | 24 V 24 V | |
| <ul style="list-style-type: none"> at 50 Hz rated value at 60 Hz rated value | | |
| supply voltage 1 of the light source at DC rated value | 24 V | |
| Control circuit/ Control | | |
| inrush current of LED module maximum | 2 A | |
| Auxiliary circuit | | |
| design of the contact of auxiliary contacts | Silver alloy | |
| number of NC contacts for auxiliary contacts | 0 | |
| number of NO contacts for auxiliary contacts | 1 | |
| Connections/ Terminals | | |
| type of electrical connection | spring-loaded terminals | |
| <ul style="list-style-type: none"> of modules and accessories | Spring-type terminal | |
| type of connectable conductor cross-sections | 2x (0.25 ... 1.5 mm ²) 2x (0.25 ... 0.75 mm ²) 2x (0.25 ... 1.5 mm ²) 2x (24 ... 16) | |
| <ul style="list-style-type: none"> solid without core end processing finely stranded with core end processing finely stranded without core end processing at AWG cables | | |
| tightening torque of the screws in the bracket | | 1 ... 1.2 N·m |
| | | |
| Lamp | | |
| type of light source | LED | |
| color of the light source | yellow | |
| light intensity | 900 ... 1 400 mcd | |
| Ambient conditions | | |
| ambient temperature | -25 ... +70 °C -40 ... +80 °C | |
| <ul style="list-style-type: none"> during operation during storage | | |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3K6 (with relative air humidity of 10 ... 95%, no condensation in operation permitted for all devices behind front panel) | |
| Installation/ mounting/ dimensions | | |
| fastening method | front plate mounting | |
| <ul style="list-style-type: none"> of modules and accessories | Front plate mounting | |

| | |
|---|---------|
| height | 40 mm |
| width | 30 mm |
| shape of the installation opening | round |
| mounting diameter | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm |
| mounting height | 11 mm |
| installation width | 29.5 mm |
| installation depth | 49.7 mm |

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1132-0AB30-3BA0-Z Y19>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1132-0AB30-3BA0-Z Y19>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1132-0AB30-3BA0-Z Y19>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1132-0AB30-3BA0-Z Y19&lang=en

last modified:

1/26/2022 