

LINEAR TECHNOLOGY MATERIALS DECLARATION

lt1781isw#pbf

(Engineering Calculation)

SOIC WIDE

(printed on: 2020-07-11 20:17:06)

TOTAL MASS (g) : 0.248781

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|----------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.004106 | 1000000 | 16504.4511719 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.138021 | 975000 | 554788.375 | | |
| | | Iron (Fe) | 7439-89-6 | 0.003397 | 24000 | 13654.5595703 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000042 | 300 | 168.822921753 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000099 | 700 | 397.939758301 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.141559 | 1000000 | 569009.6875 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.004771 | 1000000 | 19178.9609375 | | |
| | | External Plating Total: | | | | 0.004771 | 1000000 | 19178.9609375 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.001132 | 1000000 | 4550.18017578 | | |
| Internal Plating Total: | | | | 0.001132 | 1000000 | 4550.18017578 | | |
| Die Attach | ELECTRICALLY CONDUCTIVE ADHESIVE | Silver (Ag) | 7440-22-4 | 0.001132 | 750000 | 4550.18017578 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000377 | 250000 | 1515.38671875 | | |
| Die Attach Total: | | | | 0.001509 | 1000000 | 6065.56640625 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.009816 | 103000 | 39456.3320312 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.085294 | 895000 | 342847.21875 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000191 | 2000 | 767.742370605 | | |
| | | Encapsulation Total: | | | | 0.095301 | 1000000 | 383071.3125 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000403 | 1000000 | 1619.89624023 | | |
| | | | | | TOTAL MASS (g) : | 0.248781 | | |