



Metric table

Dimensions in: millimeters - inches

| d ₁ | d ₂ Thread VB-FP | VB-FP-H | | | d ₃ | d ₄ | h ₁ | h ₂ | t |
|----------------|-----------------------------------|---------|-----|------|----------------|----------------|----------------|----------------|-----------|
| 20 .79 | M 6 | - | - | - | 13 .51 | 7.5 .30 | 15 .59 | 7 .28 | 11 .43 |
| 30 1.18 | M 5 | M 6 | M 8 | - | 17 .67 | 9 .35 | 24 .94 | 11 .43 | 15 .59 |
| 40 1.57 | - | - | - | M 6 | M 8 | M 10 | 21 .83 | 13 .43 | 18 .71 |
| 50 1.97 | - | - | - | M 8 | M 10 | M 12 | 24 .94 | 15 .59 | 18 .71 |
| 60 2.36 | - | - | - | M 12 | - | - | 28 1.10 | 15 .59 | 25 .98 |
| 60 2.36 | - | - | - | M 16 | - | - | 28 1.10 | 15 .59 | 25 .98 |
| 70 2.76 | - | - | - | M 16 | - | - | 32 1.26 | 21 .83 | 25 .98 |

Specification

- Six-lobed knob
Phenolic plastic
 - Temperature resistant up to 300 °F (150 °C)
 - Black, shiny finish
- Tapped insert
Brass, molded-in
- RoHS compliant

Information

VB-FP and VB-FP-H six-lobed knobs offer a wide range of clamping.

see also...

- Six-Lobed Knobs VB (with Blind Tapped Insert)
- Six-Lobed Knobs VP (Solid Type, with Steel Threaded Stud)
- Six-Lobed Knobs VP-H (Hollow Type, with Steel Threaded Stud)

On request

- For certain minimum quantities, stainless steel inserts

| | | |
|---|---|--------------------------------|
| How to order (Solid type) 1 2 VB-FP-20-M6 | 1 | Handle diameter d ₁ |
| | 2 | Thread d ₂ |
| How to order (Hollow type) 1 2 VB-FP-H-40-M8 | 1 | Handle diameter d ₁ |
| | 2 | Thread d ₂ |