

Specification Sheet

Part Number: 151-00194

HellermannTyton Connector Clips provide a single method to mount connectors to various surfaces in a variety of applications. Highly engineered designs feature anti-rattle discs, anti-rotation oval fir trees and clamps for mounting on edges.



An assortment of Connector Clips is available to fit the variety of connector slot designs made by most of the largest global connector manufacturers.

Conn. Clip w/Oval Arrowhead, 0.8-2.0mm Panel Thick, 7.0x12.0mm Hole Dia, PA66HIRHS, Black, 500/pkg

Article Number 151-00194

Type CCSFT7x12

Color Black (BK)

Quantity Per bag

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Conn. Clip w/Oval Arrowhead, 0.8-2.0mm Panel Thick, 7.0x12.0mm Hole Dia, PA66HIRHS, Black, 500/pkg
Global Part Name	CCSFT7x12-PA66HIRHS-BK
Length L (Imperial)	0.63
Length L (Metric)	17.5
Fixation Method	Arrowhead for oval holes
Width W (Metric)	17.5
Height H (Imperial)	0.69
Height H (Metric)	17.6
Panel Thickness Min (Imperial)	0.08
Panel Thickness Max (Imperial)	0.31
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	2.0
Mounting Hole Diameter D (Imperial)	0.28 - 0.47
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm
Mounting Hole Diameter D Min (Imperial)	0.275

Mounting Hole Diameter D Max (Imperial) 0.472

Mounting Hole Diameter D Max (Metric) 12.0

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

UV Resistant (Yes/No) No

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

