



Inch | Metric



**elesa**  
Original design VC.192 / VC.254

**SS** Stainless Steel

**3** Type

- E** With tapped blind bore
- D** With tapped through bore

**Specification**

- Five-lobed knob  
Plastic  
Duroplast (Phenolic PF)  
- Temperature resistant up to 203 °F (110 °C)  
- Black, shiny finish
- **EN 5337**  
Tapped insert  
- Brass  
- Steel (inch threads with  $d_1 = 2.36''-3.35''$ )
- **EN 5337.5**  
Stainless steel AISI 303
- *Plastic Characteristics* → page 2135
- *Stainless Steel Characteristics* → page 2143
- **RoHS compliant**

**On request**

- Plain blind bore

**Information**

EN 5337 and EN 5337.5 five-lobed knobs, which offer the fingers a secure grip, are solid, so that there are no cavities where unhealthy residues may be deposited.

Resistant to solvents, oils, grease and other chemical agents.

see also...

- *Five-Lobed Knobs EN 5337.2 (Technopolymer Plastic)* → page 600
- *Solid Five-Lobed Knobs EN 5337.4 (Technopolymer Plastic)* → page 606

How to order (Metric, brass / steel insert)	1 Handle diameter $d_1$
1 2 3	2 Thread $d_2$
<b>EN5337-50-M10-D</b>	3 Type
How to order (Inch, stainless steel insert)	1 Handle diameter $d_1$
1 2 3	2 Thread $d_2$
<b>EN5337.5-40-5/16X18-E</b>	3 Type

### Inch table

Dimensions in: inches - millimeters

1 <b>d<sub>1</sub></b>	2 <b>d<sub>2</sub></b> Thread EN 5337 Type E		EN 5337.5 Type E	<b>d<sub>4</sub></b>	<b>h<sub>1</sub> +0.04</b>	<b>h<sub>2</sub> +0.04</b>	<b>t<sub>1</sub></b> min.
1.26 32	1/4 x 20	-	1/4 x 20	0.75 19	0.91 23	0.43 11	0.47 12
1.57 40	1/4 x 20	5/16 x 18	5/16 x 18	0.83 21	1.06 27	0.47 12	0.51 13
1.97 50	5/16 x 18	3/8 x 16	3/8 x 16	0.98 25	1.30 33	0.55 14	0.67 17
2.36 60	3/8 x 16*	1/2 x 13*	-	1.06 27	1.46 37	0.67 17	0.79 20
2.76 70	1/2 x 13*	-	-	1.18 30	1.73 44	0.79 20	0.79 20
3.35 85	5/8 x 11*	-	-	1.38 35	2.13 54	1.18 30	0.87 22

### Metric table

Dimensions in: millimeters - inches

1 <b>d<sub>1</sub></b>	2 <b>d<sub>2</sub></b> Thread EN 5337 Type E				<b>d<sub>3</sub></b>	<b>d<sub>4</sub></b>	<b>h<sub>1</sub> +1</b>	<b>h<sub>2</sub> +1</b>	<b>h<sub>3</sub></b>	<b>t<sub>1</sub></b> min.	<b>t<sub>2</sub></b>
	Type E	Type D	Type E	Type E							
32 1.26	M 6	-	-	M 6	-	19 0.75	23 0.91	11 0.43	-	12 0.47	-
40 1.57	M 6	M 8	M 8	M 8	14 0.55	21 0.83	27 1.06	12 0.47	1.5 0.06	13 0.51	18 0.71
50 1.97	M 8	M 10	M 10	M 10	16 0.63	25 0.98	33 1.30	14 0.55	1.5 0.06	17 0.67	22 0.87
60 2.36	M 10	M 12	M 12	M 12	17 0.67	27 1.06	37 1.46	17 0.67	1.5 0.06	20 0.79	26 1.02
70 2.76	M 12	-	M 12	-	17 0.67	30 1.18	44 1.73	20 0.79	1.5 0.06	20 0.79	26 1.02
85 3.35	M 16	-	M 16	-	24 0.94	35 1.38	54 2.13	30 1.18	2 0.08	22 0.87	35 1.38

\*These sizes have a steel tapped insert

1.1  
1.2  
1.3  
1.4  
2.1  
2.2  
2.3  
2.4

