


THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO CW INDUSTRIES INCORPORATED AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN CW INDUSTRIES PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM CW INDUSTRIES INCORPORATED, SOUTHAMPTON, PENNSYLVANIA USA.

Rating	20A 125V AC, 16A 250V AC		
Contact Resistance	50m ohm max.		
Insulation Resistance	DC 500V 100M ohm min.		
Dielectric Strength	AC 1500V 1 minute		
Operating Temperature	-25° C ~ 85° C		
Switch Function	2P SPST ON - OFF	Cut-Out 1.0 ~ 3.0 mm thk.	

MATERIAL:
Frame: Nylon 66 (94 v-2), Black
Actuator: Nylon 66 (94 v-2), Black
Terminals: Silver plated Copper alloy.
Printed: White, Hot stamping



RoHS Compliant	1 Revised 7/14/2010 - Added I O to button.		
 Southampton, Pa. 18966 Tel 215.355.7080/www.cwind.com	Date Drawn: 12/21/09	Rev. 1	Unit: mm
	Title: ROCKER SWITCH		Checked By: G.Guld
		CW P/N: GRB293A01BB	