

R41BW410000TOK

Aliases (41BW410000TOK)

R41B, Film, Metallized Polypropylene, Automotive Safety, 1 uF, 10%, 350 VAC (Y2), 125°C, Lead Spacing = 37.5mm



Click [here](#) for the 3D model.

Dimensions

L	41.5mm +0.3/-0.5mm
H	40mm +0.1/-0.5mm
T	20mm +0.2/-0.5mm
S	37.5mm +/-0.4mm
LL	4mm +2mm
F	1mm +/-0.05mm

Packaging Specifications

Packaging	Tray
Packaging Quantity	126

General Information

Series	R41B
Dielectric	Metallized Polypropylene
Style	Radial
Features	Automotive Grade, EMI Safety
RoHS	Yes
Lead	Cut
Safety Class	Y2
Qualifications	AEC-Q200, ENEC, UL, cUL, CQC
AEC-Q200	Yes
THB Performance	Yes
Component Weight	38.87 g

Specifications

Capacitance	1 uF
Capacitance Tolerance	10%
Voltage AC	350 VAC (Y2)
Temperature Range	-40/+125°C
Rated Temperature	125°C
Dissipation Factor	0.2% 1kHz
Insulation Resistance	30 GOhms
Max dV/dt	300 V/us