


## HEIDI-W

~30° wide beam optimized for LUXEON Rebel ES


### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	11.7 mm
Fastening	tape, pin
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	11.1 kg
Quantity in Box	3264 pcs
ROHS compliant	yes ⓘ



### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
HEIDI-W	Single lens	PMMA	clear
HEIDI-TAPE	Tape	PU tape	black




This drawing is our property. It can't be reproduced or communicated without our written agreement.		<b>LEDiL</b>		Ledil Oy Joensuunkatu 13 FIN-24100 SALO Finland	
<b>DRAWING TITLE</b>		<b>Datasheet Heidi-Series Assy</b>			
<b>DRAWN BY</b> ah	<b>DATE</b> 1.2.2012	<b>SIZE</b> A4	<b>DRAWING NUMBER</b>		<b>REV</b> 2
<b>CHECKED BY</b>	<b>DATE</b>	<b>SCALE</b> 2:1	<b>WEIGHT (g)</b>	<b>SHEET</b> 1/1	
<b>DESIGNED BY</b>	<b>DATE</b>				



#### PHOTOMETRIC DATA (MEASURED):





LED XHP35 HD  
 FWHM 32.0°  
 Efficiency 84 %  
 Peak intensity 2.410 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED XHP35 HI  
 FWHM 31.0°  
 Efficiency 94 %  
 Peak intensity 2.700 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED XP-G3  
 FWHM 32.0°  
 Efficiency 94 %  
 Peak intensity 2.500 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED XP-L HD  
 FWHM 33.0°  
 Efficiency 87 %  
 Peak intensity 2.450 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (MEASURED):


#### LUMILEDS

LED LUXEON Rebel  
 FWHM 32.0°  
 Efficiency 87 %  
 Peak intensity 2.800 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### LUMILEDS

LED LUXEON Rebel ES  
 FWHM 32.0°  
 Efficiency 87 %  
 Peak intensity 2.800 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### NICHIA

LED NVSW219D  
 FWHM 32.0°  
 Efficiency 94 %  
 Peak intensity 2.600 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:











#### NICHIA


LED NVSW319B  
 FWHM 32.0°  
 Efficiency 94 %  
 Peak intensity 2.600 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):

<p><b>NICHIA</b></p> <p>LED NVSW3x9A            FWHM 31.0°            Efficiency 90 %            Peak intensity 2.400 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>NICHIA</b></p> <p>LED NWSx229A            FWHM 31.0°            Efficiency 83 %            Peak intensity 2.300 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED OSLON SSL 150            FWHM 32.0°            Efficiency 86 %            Peak intensity 2.900 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED Z5M3            FWHM 32.0°            Efficiency 94 %            Peak intensity 2.500 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		

## PHOTOMETRIC DATA (MEASURED):






### PHOTOMETRIC DATA (SIMULATED):



LED XP-G2 HE  
FWHM 32.0°  
Efficiency 93 %  
Peak intensity 2.562 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED LUXEON A  
FWHM 31.0°  
Efficiency %  
Peak intensity cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED LUXEON IR Domed 150  
FWHM 31.0°  
Efficiency 93 %  
Peak intensity 0.000 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



LED LUXEON IR Domed 90  
FWHM 31.0°  
Efficiency 94 %  
Peak intensity 0.000 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:


#### PHOTOMETRIC DATA (SIMULATED):

##### LUMILEDS

LED LUXEON R  
 FWHM 32.0°  
 Efficiency %  
 Peak intensity cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:


##### LUMILEDS

LED LUXEON SunPlus 20 Line (120 deg)  
 FWHM 31.0°  
 Efficiency 95 %  
 Peak intensity 3.101 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### LUMILEDS

LED LUXEON SunPlus 20 Line (150 deg)  
 FWHM 31.0°  
 Efficiency 92 %  
 Peak intensity 2.940 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:






##### LUMILEDS

LED LUXEON SunPlus 20 Line (150 deg)  
 FWHM 31.0°  
 Efficiency 91 %  
 Peak intensity 2.883 cd/m  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### PHOTOMETRIC DATA (SIMULATED):

<p><b>LUMILEDS</b></p> <p>LED LUXEON SunPlus 35 Line            FWHM 31.0°            Efficiency 94 %            Peak intensity 3.120 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>NICHIA</b></p> <p>LED NVSxE21A            FWHM 31.0°            Efficiency 93 %            Peak intensity 2.761 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED OSCONIQ P 3737 Flat            FWHM 32.0°            Efficiency 95 %            Peak intensity 2.864 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)