# ATGBICS MSA Industry Standard Compatible Transceiver SFP28 25GBase-ER (1310nm, SMF, 40km, DOM, Ind Temp)

**Brand :** ATGBICS

**Product code:** SFP-25G-ER-I-MSA-AT

**Product name :** ATGBICS MSA Industry Standard Compatible Transceiver SFP28 25GBase-ER (1310nm, SMF, 40km, DOM, Ind Temp)

ATGBICS MSA Industry Standard Compatible Transceiver SFP28 25GBase-ER (1310nm, SMF, 40km, DOM, Ind Temp)

ATGBICS MSA Industry Standard Compatible Transceiver SFP28 25GBase-ER (1310nm, SMF, 40km, DOM, Ind Temp):

ATGBICS SFP-25G-ER-I-MSA-AT 25GBase-ER supports a distance of up to 40km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC connector. This product is suitable for rugged environments and can operate at temperatures between -40C to +85C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets all Multi-Source Agreement (MSA) standards for this form factor and are uniquely serialised for full date code and BOM traceability. We proudly offer a compatibility guarantee and lifetime replacement warranty.

## Performance

| | |
|---|---|
| SFP transceiver type * | Fiber optic |
| Maximum data transfer rate * | 25000 Mbit/s |
| Interface type * | SFP28 |
| Single-mode fiber (SMF) supported | ✔ |
| Multi-mode fiber (MMF) supported | ✘ |
| Fiber optic connector | LC |
| SFP transceiver standard | ER |
| Maximum transfer distance | 40000 m |
| Wavelength | 1310 nm |
| Ethernet LAN | ✔ |
| Ethernet interface type | 25 Gigabit Ethernet |
| Digital Diagnostics Monitoring (DDM) | ✔ |
| Wavelength-division multiplexing (WDM) | ✘ |

## Features

| | |
|---|---|
| Product colour | Silver |
| Housing material | Metal |
| Plug and Play | ✔ |
| Hot-Plug support | ✔ |
| Hot-swap | ✔ |
| Easy to install | ✔ |
| Country of origin | United Kingdom |
| Brand compatibility | MSA Compliant |
| Certification | CE, FCC, RoHS |

## Power

| | |
|---|---|
| Input voltage | 3.3 V |
| Maximum voltage | 3.5 V |
| Power consumption (typical) | 1 W |

## Operational conditions

| | |
|---|---|
| Minimum operating temperature | -40 °C |
| Maximum operating temperature | 85 °C |
| Operating temperature (T-T) | -40 - 85 °C |
| Storage temperature (T-T) | -40 - 85 °C |
| Operating relative humidity (H-H) | 0 - 95% |
| Storage relative humidity (H-H) | 0 - 95% |

## Weight & dimensions

| | |
|---|---|
| Width | 13.4 mm |
| Depth | 56.5 mm |
| Height | 8.5 mm |
| Weight | 19 g |

## Packaging data

| | |
|---|---|
| Number of products included | 1 pc(s) |
| Package type | Box |

## Technical details

| | |
|---|---|
| Sustainability compliance | ✔ |
| Sustainability certificates | RoHS |
| Doesn't contain | Lead |

5056468773852