

## Specification Sheet

Part Number: T50ML0M4



Screw mount style creates low insertion and high extraction force.

Choose from several tensile strengths and lengths to accommodate a range of applications.

1-Pc Cable Tie/Screw Mount, 15.4" Long, #10 Screw, 4.0" Max Bundle Dia, 50lb, PA66, Black, 1000/pkg

**Article Number** 113-00035

**Type** T50ML

**Color** Black (BK)

**Quantity Per** bag

**Product Description** 1-piece Screw Mount Cable Ties fasten with a screw or bolt to provide secure routing of cable bundles. Multiple configurations are available to cover a range of bundle sizes and tensile strengths.

**Short Description** 1-Pc Cable Tie/Screw Mount, 15.4" Long, #10 Screw, 4.0" Max Bundle Dia, 50lb, PA66, Black, 1000/pkg

**Global Part Name** T50ML-PA66-BK

<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	15.4
<b>Length L (Metric)</b>	390.0
<b>Fixation Method</b>	Fixing hole
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.7
<b>Bundle Diameter Min (Imperial)</b>	0.12
<b>Bundle Diameter Min (Metric)</b>	3.0
<b>Bundle Diameter Max (Imperial)</b>	3.94
<b>Bundle Diameter Max (Metric)</b>	100.0
<b>Height H (Imperial)</b>	0.23

<b>Height H (Metric)</b>	5.84
<b>Mounting Hole Diameter D (Imperial)</b>	0.22
<b>Mounting Hole Diameter D (Metric)</b>	5.5 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	5.5
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL
<b>UL Recognized (US)</b>	Yes
<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>UL Listed (US)</b>	Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988